



FCS-3085 Version: 1

## Zoom Dome Outdoor Network camera, 4-Megapixel, Outdoor, 802.3af PoE, day & night, IR LEDs, WDR, Varifocal

### Key Features

- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Weatherproof IP66-rated with wide operating temperature (-30°C to 60°C) for harsh environments
- Built-in Micro SDHC/SDXC card slot for local storage
- Built-in infrared LEDs for night viewing up to 30m
- Removable IR-cut filter for day and night surveillance
- Vandal-proof IK10-rated housing
- Compression: H.264/MJPEG
- Power support: PoE (IEEE 802.3af)
- Free video surveillance and CMS (Central Management System) software with 64-channel license

### Specifications

#### System Specifications

##### Standards & Protocols:

TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

##### Image Sensor:

1/3" Progressive Scan CMOS

##### Connectors and Cabling:

1 x RJ-45 10/100 Mbps PoE port

Power Connector

Audio:In/Out

I/O terminal block (1 DI/1 DO)

1 x MicroSDHC/ MicroSDXC card slot

##### Button/Knob:

Reset Button

##### Indicator:

Power

**Lens:**

2.8 - 12 mm @ F1.4,

**IR Cut Filter:**

IR cut filter with auto switch

**IR LED:**

Up to 30m

**Shutter Time:**

1/3 s ~ 1/10,000 s

**Angle of View:**

112°~33.8°

**Video Compression:**

H.264/MJPEG/H.264+

**Resolution:**

50Hz: 20fps (2688×1520), 25fps(1920×1080), 25fps(1280×720)

60Hz: 20fps (2688×1520), 30fps (1920×1080), 30fps(1280×720)

**Video Format:**

RAW

**Audio Compression:**

G.711/G.722.1/G.726/MP2L2, 64Kbps(G.711) / 16Kbps(G.722.1) / 16Kbps(G.726) / 32-128Kbps(MP2L2)

**Power Input:**

12V DC±10%, PoE (802.3af)

**Power Consumption:**

Max. 5.5 W

## Features

**General:**

Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser

**PoE:**

PoE (802.3af Class3)

**Security:**

One-key reset, Anti-Flicker, heartbeat, mirror, password protection, privacy mask, Watermark, IP address filtering, Anonymous access

**Video:**

Line Crossing, Intrusion Detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect , IP address conflict, Storage exception

**Audio:**

G.711/G.722.1/G.726/MP2L2

## Performance

**Number of Clients:**

10

**Data Transfer Rate:**

32Kbps~16Mbps

**Storage Capacity:**

Support Micro SD/SDHC/SDXC card with ANR (up to 128G)

**Frame Rate:**

50Hz: 20fps , 25fps, 25fps

60Hz: 20fps , 30fps ,30fps

**Minimum illumination:**

0.01Lux @(F1.2,AGC ON), 0.014 Lux @(F1.4,AGC ON), 0 Lux with IR

## Environment

**Temperature (°C):**

-30 °C ~ 60 °C (-22 °F ~ 140 °F)

**Humidity (Non-condensing):**

Humidity 95% or less (non-condensing)

## Physical Specifications

**Dimensions (W x D x H mm):**

140

**Weight (g):**

140

**Color:**

99.0

## Approval and Compliance

**EMI/EMS:**

CE,FCC

**Environmental Test:**

IEC60068-2-75Eh, 50J; EN50102, IK10

**Others:**

ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI

## Others

**Operation Systems:**

Microsoft Windows 10/8/7/Vista/XP/

**Viewing Systems:**

IE

---

## Order Information

FCS-3085

---

## Package Contents

FCS-3085

Screw Kit

Resource CD (User Manual, Utility, QIG)

---

## Optional Accessory



**CAS-7303**

Vertical pole mount

No liability or responsibility for any errors or omissions in the content.  
Specifications are subject to change without notice.  
All mentioned brand names are registered trademarks and property of their owners.  
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.