

## IBM SAS 2.5-inch Hybrid Hard Drives for System x

### IBM Redbooks Product Guide

The IBM® SAS 2.5-inch Hybrid hard disk drives (HDDs) for IBM System x® provide cost-effective performance and density by combining a cache of NAND flash and conventional HDD media in a single industry-standard small form factor (SFF) drive. These hybrid drives accelerate HDD performance for small and medium business and distributed large enterprise application environments, enabling higher I/O performance for most frequently used data while leveraging the capacity and cost of spinning media for primary storage.

Figure 1 shows the IBM SAS 2.5-inch Hybrid HDD.



Figure 1. IBM SAS 2.5-inch Hybrid HDD

### Did you know

While conventional hard disk drives can meet capacity requirements, HDD performance enhancements have remained relatively flat and confined to the rotational speed of the media. Hybrid HDDs offer accelerated performance by utilizing integrated NAND flash to cache data. The result is significantly improved performance over today's conventional HDDs.

Rigorous testing of 2.5-inch Hybrid HDDs by IBM through the IBM ServerProven® program assures a high degree of confidence in storage subsystem compatibility and reliability. Providing additional peace of mind, these drives are covered under IBM warranty.

## Part number information

Table 1 lists the information for ordering part numbers and feature codes for the IBM SAS Hybrid HDDs.

Table 1. Ordering part numbers and feature codes

Description	Part number	Feature code
Hot-swap drives		
IBM 600GB 10K 6Gbps SAS 2.5" G2HS Hybrid	00AD102	A4G7
Simple-swap drives		
IBM 600GB 10K 6Gbps SAS 2.5" G2SS Hybrid	00AD107	A4G8

The part numbers include the following items:

- One Hybrid HDD with a hot-swap or simple-swap drive tray
- Warranty Flyer
- *Important Notices* document

## Features

The IBM SAS 2.5-inch Hybrid HDDs have the following features:

- Industry standard 2.5-inch form factor supports 2.5-inch drive bays on selected System x, IBM iDataPlex®, IBM BladeCenter® and IBM Flex System™ servers.
- Combine a cache of NAND flash and conventional media to accelerate hard disk drive performance.
- Enable higher IO performance while leverage the capacity and cost of spinning media for primary storage.
- Bring transparent enhanced performance to data with high locality (*hot* data).
- Transparently cache data at I/O block level.
- Improve performance of server internal storage in lower cost configurations, without a need to utilize SSDs and storage tiering.
- Performance features:
  - 128 MB DRAM data buffer
  - 16 GB Hybrid read cache
  - 8 MB Hybrid NVC-backed write cache
  - Support up to 6 Gbps SAS interface speeds
  - 128 queue depth
- Reliability features:
  - ECC maximum burst correction length of 530 bits
  - S.M.A.R.T. (self-monitoring, analysis, and reporting technology) support
  - Drive Self Test (DST)
  - Background Media Scan (BMS)
  - Idle Read After Write (IRAW)

Hybrid HDDs integrate three media types: HDD, DRAM, and NAND. HDD memory is used as a primary data storage for all data. DRAM memory is used for buffering all reads and caching all writes. NAND memory is divided into two parts: eMLC flash memory is used as a read cache for frequently used data; and SLC flash memory is used as a non-volatile storage for write cache in DRAM in case of a power failure.

## Technical specifications

Table 2 presents technical specifications for the IBM SAS 2.5-inch Hybrid HDDs.

Table 2. IBM SAS 2.5-inch Hybrid HDD technical specifications

Specification	600 GB	
Part number	00AD102	00AD107
Interface	6 Gbps SAS	6 Gbps SAS
Hot-swap drive	Yes	No
Form factor	2.5-inch	2.5-inch
Capacity	600 GB	600 GB
Rotational speed	10,000	10,000
Data reliability	< 1 in 10 <sup>16</sup> bits read	< 1 in 10 <sup>16</sup> bits read
MTBF, hours	2,000,000	2,000,000
Average sustained transfer rate	151 MBps	151 MBps
Average rotational latency	2.9 ms	2.9 ms
Shock	40 <i>g</i> , 11 ms; 25 <i>g</i> , 2 ms	40 <i>g</i> , 11 ms; 25 <i>g</i> , 2 ms
Vibration, operating	5-500 Hz at 0.5 <i>g</i>	5-500 Hz at 0.5 <i>g</i>
Vibration, non-operating	5-500 Hz at 3.0 <i>g</i>	5-500 Hz at 3.0 <i>g</i>
Typical power	< 7.5 W	< 7.5 W

## Supported servers

The compatibility information for the IBM SAS 2.5-inch Hybrid HDDs and System x, iDataPlex, and NeXtScale servers is shown in Table 3 (Parts 1, 2, and 3).

Table 3. System x, iDataPlex, and NeXtScale compatibility (Part 1)

Part number	Description	x3250 M5 (5458)	x3500 M4 (7383, E5-2600 v2)	x3550 M4 (7914, E5-2600 v2)	x3650 M4 (7915, E5-2600 v2)	x3650 M4 HD (5460)	dx360 M4 (7912, E5-2600 v2)	nx360 M4 (5455)
00AD102	IBM 600GB 10K 6Gbps SAS 2.5" G2HS Hybrid	N	Y	Y	Y	N	N	N
00AD107	IBM 600GB 10K 6Gbps SAS 2.5" G2SS Hybrid	N	N	N	N	N	Y	N

Table 3. System x, iDataPlex, and NeXtScale compatibility (Part 2)

Part number	Product description	x3100 M4 (2582)	x3250 M4 (2583)	x3300 M4 (7382)	x3500 M4 (7383, E5-2600)	x3530 M4 (7160)	x3550 M4 (7914, E5-2600)	x3630 M4 (7158)	x3650 M4 (7915, E5-2600)	x3690 X5 (7147)	x3750 M4 (8722)	x3850 X5 (7143)	dx360 M4 (7912, E5-2600)
00AD102	IBM 600GB 10K 6Gbps SAS 2.5" G2HS Hybrid	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	N
00AD107	IBM 600GB 10K 6Gbps SAS 2.5" G2SS Hybrid	N	Y	N	N	Y	N	N	N	N	N	N	Y

Table 3. System x, iDataPlex, and NeXtScale compatibility (Part 3)

Part number	Product description	x3200 M3 (7327, 7328)	x3250 M3 (4251, 4252)	x3400 M3 (7378, 7379)	x3500 M3 (7380)	x3550 M3 (7944)	x3620 M3 (7376)	x3630 M3 (7377)	x3650 M3 (7945)	x3755 M3 (7164)	dx360 M3 (6391)
00AD102	IBM 600GB 10K 6Gbps SAS 2.5" G2HS Hybrid	N	N	N	N	Y	N	Y	Y	N	N
00AD107	IBM 600GB 10K 6Gbps SAS 2.5" G2SS Hybrid	N	N	N	N	N	N	N	N	N	N

The compatibility information for the IBM SAS 2.5-inch Hybrid HDDs and BladeCenter and Flex System servers is shown in Table 4.

Table 4. BladeCenter and Flex System compatibility

Part number	Product description													
		HS12 (8028)	HS22 (7870)	HS22V (7871)	HS23 (7875)	HS23E (8038)	HX5 (7872)	HX5 (7873)	x220 (7906)	x222 (7916)	x240 (8737, E5-2600)	x240 (8737, E5-2600 v2)	x440 (7917)	
00AD102	IBM 600GB 10K 6Gbps SAS 2.5" G2HS Hybrid	N	Y	N	Y	Y	N	N	Y	N	Y	Y	Y	
00AD107	IBM 600GB 10K 6Gbps SAS 2.5" G2SS Hybrid	N	N	N	N	N	N	N	N	N	N	N	N	

See the IBM ServerProven® website for the latest compatibility information for System x, BladeCenter, iDataPlex, and Flex System servers: <http://ibm.com/servers/eserver/serverproven/compat/us/>

## Supported storage controllers

The IBM SAS 2.5-inch Hybrid HDDs require a supported disk controller. Tables 5 and 6 list the System x, BladeCenter, and Flex System controllers that support these Hybrid HDDs installed in a supported server.

Table 5. RAID controllers for System x and iDataPlex servers supported with Hybrid HDDs (Part 1)

Part number	Product description	x3250 M5 (5458)	x3500 M4 (7383, E5-2600 v2)	x3550 M4 (7914, E5-2600 v2)	x3650 M4 (7915, E5-2600 v2)	x3650 M4 HD (5460)	dx360 M4 (7912, E5-2600 v2)	nx360 M4 (5455)
Onboard	ServeRAID M5210e SAS/SATA Controller	N	N	N	N	Y	N	N
46C9110	ServeRAID M5210 SAS/SATA Controller	N	Y*	Y*	Y*	Y	N	N
Onboard	ServeRAID M5110e SAS/SATA Controller	N	N	N	Y	N	N	N
81Y4481	ServeRAID M5110 SAS/SATA Controller	N	Y	Y	Y	N	Y	N
81Y4448	ServeRAID M1115 SAS/SATA Controller	N	Y	Y	N	N	Y	N
81Y4492	ServeRAID H1110 SAS/SATA Controller	N	N	Y	N	Y	Y	N
90Y4304	ServeRAID M5016 SAS/SATA Controller	N	N	N	N	N	N	N
46M0829	ServeRAID M5015 SAS/SATA Controller	N	N	N	N	N	N	N
46M0916	ServeRAID M5014 SAS/SATA Controller	N	N	N	N	N	N	N
46M0831	ServeRAID M1015 SAS/SATA Controller	N	N	N	N	N	N	N
Onboard	ServeRAID C100 / C105	N	N	N	N	N	N	N
46M0912	IBM 6Gb Performance Optimized HBA	N	Y	Y	Y	N	Y	N
46C8988	N2115 SAS/SATA HBA	N	Y	Y	Y	N	N	N
47C8675	N2215 SAS/SATA HBA	N	Y*	Y*	Y*	Y	N	N

\* Support is planned for later in 2013

Table 5. RAID controllers for System x and iDataPlex servers supported with Hybrid HDDs (Part 2)

Part number	Product description												
		x3100 M4 (2582)	x3250 M4 (2583)	x3300 M4 (7382)	x3500 M4 (7383, E5-2600)	x3530 M4 (7160)	x3550 M4 (7914, E5-2600)	x3630 M4 (7158)	x3650 M4 (7915, E5-2600)	x3690 X5 (7147)	x3750 M4 (8722)	x3850 X5 (7143)	dx360 M4 (7912, E5-2600)
Onboard	ServeRAID M5210e SAS/SATA Controller	N	N	N	N	N	N	N	N	N	N	N	N
46C9110	ServeRAID M5210 SAS/SATA Controller	N	N	N	Y*	N	Y*	N	Y*	N	N	N	N
Onboard	ServeRAID M5110e SAS/SATA Controller	N	N	N	N	N	N	N	Y	N	Y	N	N
81Y4481	ServeRAID M5110 SAS/SATA Controller	N	N	Y	Y	Y	Y	N	Y	N	Y	N	Y
81Y4448	ServeRAID M1115 SAS/SATA Controller	N	N	Y	Y	Y	Y	N	N	N	Y	N	Y
81Y4492	ServeRAID H1110 SAS/SATA Controller	Y	Y	Y	N	Y	Y	N	N	N	N	N	Y
90Y4304	ServeRAID M5016 SAS/SATA Controller	N	N	N	N	N	N	N	N	Y	N	Y	N
46M0829	ServeRAID M5015 SAS/SATA Controller	Y	Y	N	N	N	N	N	N	Y	N	Y	N
46M0916	ServeRAID M5014 SAS/SATA Controller	Y	Y	N	N	N	N	N	N	Y	N	Y	N
46M0831	ServeRAID M1015 SAS/SATA Controller	Y	Y	N	N	N	N	N	N	Y	N	Y	N
Onboard	ServeRAID C100 / C105	N	N	N	N	N	N	N	N	N	N	N	N
46M0912	IBM 6Gb Performance Optimized HBA	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	Y
46C8988	N2115 SAS/SATA HBA	N	N	N	Y	N	Y	N	Y	N	Y	Y	N
47C8675	N2215 SAS/SATA HBA	N	N	N	Y*	N	Y*	N	Y*	N	N	N	N

\* Support is planned for later in 2013

Table 5. RAID controllers for System x and iDataPlex servers supported with Hybrid HDDs (Part 3)

Part number	Product description	x3200 M3 (7327, 7328)	x3250 M3 (4251, 4252)	x3400 M3 (7378, 7379)	x3500 M3 (7380)	x3550 M3 (7944)	x3620 M3 (7376)	x3630 M3 (7377)	x3650 M3 (7945)	x3755 M3 (7164)	dx360 M3 (6391)
Onboard	ServeRAID M5110e SAS/SATA Controller	N	N	N	N	N	N	N	N	N	N
81Y4481	ServeRAID M5110 SAS/SATA Controller	N	N	N	N	N	N	N	N	N	N
81Y4448	ServeRAID M1115 SAS/SATA Controller	N	N	N	N	N	N	N	N	N	N
81Y4492	ServeRAID H1110 SAS/SATA Controller	N	N	N	N	Y	N	N	Y	N	N
90Y4304	ServeRAID M5016 SAS/SATA Controller	N	N	N	N	Y	N	N	Y	N	N
46M0829	ServeRAID M5015 SAS/SATA Controller	N	N	N	N	Y	N	Y	Y	N	N
46M0916	ServeRAID M5014 SAS/SATA Controller	N	N	N	N	Y	N	Y	Y	N	N
46M0831	ServeRAID M1015 SAS/SATA Controller	N	N	N	N	Y	N	Y	Y	N	N
Onboard	ServeRAID C100 / C105	N	N	N	N	N	N	N	N	N	N
46M0912	IBM 6Gb Performance Optimized HBA	N	N	N	N	Y	N	Y	Y	N	N
46C8988	N2115 SAS/SATA HBA	N	N	N	N	N	N	N	N	N	N
47C8675	N2215 SAS/SATA HBA	N	N	N	N	N	N	N	N	N	N

Table 6. RAID controllers for BladeCenter and Flex System servers supported with Hybrid HDDs

Part number	Product description	HS12 (8028)	HS22 (7870)	HS22V (7871)	HS23 (7875)	HS23E (8038)	HX5 (7872)	HX5 (7873)	x220 (7906)	x222 (7916)	x240 (8737, E5-2600)	x240 (8737, E5-2600 v2)	x440 (7917)
90Y4390	ServeRAID M5115 SAS/SATA Controller	N	N	N	N	N	N	N	Y	N	Y	Y	Y
90Y4750	ServeRAID H1135 Controller	N	N	N	N	Y	N	N	Y	N	N	N	N
Onboard	ServeRAID C105	N	N	N	N	N	N	N	N	N	N	N	N
Onboard	Integrated LSI SAS2004	N	N	N	Y	N	N	N	N	N	Y	Y	Y
46C7167	ServeRAID-MR10ie (CIOv) Controller	N	N	N	N	N	N	N	N	N	N	N	N
Onboard	Integrated LSI SAS1064e	N	Y	N	N	N	N	N	N	N	N	N	N
46M6908	SSD Expansion Card for IBM BladeCenter HX5	N	N	N	N	N	N	N	N	N	N	N	N



See the IBM ServerProven website for the latest information about the adapters supported by each System x server type: <http://ibm.com/servers/eserver/serverproven/compat/us/>

## Supported operating systems

Hybrid HDDs operate transparently to users, applications, databases, and operating systems. The controllers that support Hybrid HDDs are supported by the following operating systems:

- Microsoft Windows Server 2012 R2
- Microsoft Windows Server 2012
- Microsoft Windows Server 2008 R2
- Microsoft Windows Server 2008, Datacenter x64 Edition
- Microsoft Windows Server 2008, Datacenter x86 Edition
- Microsoft Windows Server 2008, Enterprise x64 Edition
- Microsoft Windows Server 2008, Enterprise x86 Edition
- Microsoft Windows Server 2008, Standard x64 Edition
- Microsoft Windows Server 2008, Standard x86 Edition
- Microsoft Windows Server 2008, Web x64 Edition
- Microsoft Windows Server 2008, Web x86 Edition
- Microsoft Windows Server 2008 Foundation
- Microsoft Windows Server 2008 HPC Edition
- Microsoft Windows HPC Server 2008
- Microsoft Windows Small Business Server 2008 Premium Edition
- Microsoft Windows Small Business Server 2008 Standard Edition
- Microsoft Windows Essential Business Server 2008 Premium Edition
- Microsoft Windows Essential Business Server 2008 Standard Edition
- Red Hat Enterprise Linux 6 Server Edition
- Red Hat Enterprise Linux 6 Server x64 Edition
- Red Hat Enterprise Linux 5 Server Edition
- Red Hat Enterprise Linux 5 Server Edition with Xen
- Red Hat Enterprise Linux 5 Server with Xen x64 Edition
- Red Hat Enterprise Linux 5 Server x64 Edition
- Red Hat Enterprise Linux 4 AS for AMD64/EM64T
- Red Hat Enterprise Linux 4 AS for x86
- SUSE Linux Enterprise Server 11 for AMD64/EM64T
- SUSE Linux Enterprise Server 11 for x86
- SUSE Linux Enterprise Server 11 with Xen for AMD64/EM64T
- SUSE Linux Enterprise Server 10 for AMD64/EM64T
- SUSE Linux Enterprise Server 10 for x86
- SUSE Linux Enterprise Server 10 with Xen for AMD64/EM64T
- SUSE Linux Enterprise Server 10 with Xen for x86
- VMware vSphere 5.1
- VMware vSphere 5.0
- VMware ESX 4.1
- VMware ESXi 4.1
- VMware ESX 4.0
- VMware ESXi 4.0

See the IBM ServerProven website for the latest information about the specific supported versions and service packs: <http://ibm.com/servers/eserver/serverproven/compat/us/>. Click **IBM System x**, then **Storage controllers & SSD adapters** to see the support matrix. Click the check mark that is associated with the System x server in question to see the details about operating system support.

## Warranty

The IBM SAS 2.5-inch Hybrid HDDs carry a one-year, customer-replaceable unit (CRU) limited warranty. When installed in a supported IBM server, these drives assume your system's base warranty and any IBM ServicePac® upgrade.

## Physical specifications

The IBM SAS 2.5-inch Hybrid HDDs have the following physical specifications.

Dimensions and weight (approximate):

- Height: 15 mm (0.6 in.)
- Width: 70 mm (2.8 in.)
- Depth: 100 mm (3.9 in.)
- Weight: 219 g (0.5 lb)

Shipping dimensions and weight (approximate):

- Height: 63 mm (2.5 in.)
- Width: 133 mm (5.2 in.)
- Depth: 174 mm (6.9 in.)
- Weight: 579 g (1.3 lb)

## Operating environment

The IBM SAS 2.5-inch Hybrid HDDs are supported in the following environment:

- Temperature: 5 - 60 °C (41 - 158°F) at -61 m to 3,048 m (-200 ft to 10,000 ft)
- Relative humidity: 5 - 90% (noncondensing)
- Maximum altitude: 2,133 m (7,000 ft)

## Agency approvals

The IBM SAS 2.5-inch Hybrid HDDs have the following agency approvals:

- UL
- CSA
- TUV
- CE Mark
- C-Tick Mark
- IEC
- Taiwan (BSMI Certification)
- Korea EMI

## Related publications

For more information, see the following documents:

- IBM US Announcement Letter - IBM 15,000 rpm SAS 2.5-inch Hybrid HDDs for System x  
<http://ibm.com/common/ssi/cgi-bin/ssialias?infotype=dd&subtype=ca&&htmlfid=897/ENUS113-156>
- IBM US Announcement Letter - IBM 10,000 rpm SAS 2.5-inch Hybrid HDDs for System x  
<http://ibm.com/common/ssi/cgi-bin/ssialias?infotype=dd&subtype=ca&&htmlfid=897/ENUS113-102>
- IBM Redbooks® publication: *IBM ServeRAID Adapter Quick Reference*  
<http://www.redbooks.ibm.com/abstracts/tips0054.html?Open>
- *IBM System x Configuration and Options Guide*  
<http://www.ibm.com/systems/xbc/cog/>
- IBM ServerProven  
<http://ibm.com/servers/eserver/serverproven/compat/us/>

# Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service. IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

*IBM Director of Licensing, IBM Corporation, North Castle Drive, Armonk, NY 10504-1785 U.S.A.*

**The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law:** INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you. This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk. IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you. Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products. This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurement may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

## COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs.

**© Copyright International Business Machines Corporation 2013. All rights reserved.**

Note to U.S. Government Users Restricted Rights -- Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

This document was created or updated on December 26, 2013.

Send us your comments in one of the following ways:

- Use the online **Contact us** review form found at:  
[ibm.com/redbooks](http://ibm.com/redbooks)
- Send your comments in an e-mail to:  
[redbook@us.ibm.com](mailto:redbook@us.ibm.com)
- Mail your comments to:  
IBM Corporation, International Technical Support Organization  
Dept. HYTD Mail Station P099  
2455 South Road  
Poughkeepsie, NY 12601-5400 U.S.A.

This document is available online at <http://www.ibm.com/redbooks/abstracts/tips1028.html> .

## Trademarks

IBM, the IBM logo, and [ibm.com](http://ibm.com) are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both. These and other IBM trademarked terms are marked on their first occurrence in this information with the appropriate symbol (® or ™), indicating US registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of IBM trademarks is available on the Web at <http://www.ibm.com/legal/copytrade.shtml>

The following terms are trademarks of the International Business Machines Corporation in the United States, other countries, or both:

BladeCenter®  
IBM Flex System™  
IBM®  
iDataPlex®  
Redbooks®  
Redbooks (logo)®  
ServerProven®  
ServicePac®  
System x®

The following terms are trademarks of other companies:

Linux is a trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.