



FCS-5102 Version: 1

**!** Power supply unit is to be ordered separately.

## Fixed IP Network Camera, 3-Megapixel, H.265/264, 4.3X Optical Zoom, 802.3af PoE, IR LEDs, Indoor/Outdoor, Vandalproof, two-way audio

The LevelOne FCS-5102 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP66 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 3-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5102 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

### Key Features

- 3-Megapixel high-definition resolution
- Video compression: H.264/H.265
- BNC connector for analog video output
- Built-in infrared LEDs for night viewing up to 30m
- Vandal-proof IK10-rated housing
- Supports 4.3X optical zoom

### Specifications

#### System Specifications

##### Standards & Protocols:

IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DDNS, DHCP, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, ICMP, SNMP, QoS

##### Image Sensor:

1/2.8"

##### Lens:

Zoom, f2.8 - 12mm / F1.4 - 2.8, P-iris

##### Connectors and Cabling:

Power connect

10/100 Mbps (PoE)

1 x Audio in

1 x Audio Out

1 x DI/DO (Terminal Block)

1 x BNC

**Button/Knob:**

Reset

**Indicator:**

Power

**IR Cut Filter:**

Support

**IR LED:**

30 Meter

**Shutter Time:**

1/5 ~ 1/16,000 sec

**Angle of View:**

90.6°~32.7°

**Pan/Tilt/Zoom:**

4.3X Optical Zoom

**Video Compression:**

H.265, H.264, MJPEG

**Resolution:**

30 fps at 2048 x 1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 720; 30 fps at 800 x 600; 30 fps at 640 x 480; 30 fps at 320 x 240

**Video Format:**

RAW

**Audio Compression:**

Mono, PCM, G.711

**Power Input:**

DC 12V

**Power Consumption:**

8W

**Data Transfer Rate:**

32 kbps -16 Mbps

## Features

**General:**

Extreme WDR (100 dB); White balance: automatic, manual; Brightness; Digital image stabilizer  
Contrast; Sharpness (auto); Auto gain control; 2D + 3D digital noise reduction; Defogging

**PoE:**

802.3af (class 3)

**Security:**

IP address filtering; HTTPs encryption; Password protected user levels; Anonymous login

**Management:**

Notify control center; Change camera settings; Command other devices; E-mail notification with snapshots;  
Upload video or snapshot to  
FTP server; Activate external device through digital output

**Video:**

Video motion detection (3 regions); External device through digital input; Sound detection; Tampering  
detection

## Performance

**Number of Clients:**

16

**Frame Rate (fps):**

30 fps at 2048 x 1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 720; 30 fps at 800 x 600; 30 fps at 640 x 480; 30 fps at 320 x 240

**Minimum illumination:**

1/5 ~ 1/16,000 sec (manual mode)

## Environment

**Temperature (°C):**

Starting Temperature: -20°C ~ 50°C (-4°F ~ 122°F) within 30 minutes

Operating Temperature: -30°C ~ 50°C (-22°F ~ 122°F)

**Humidity (Non-condensing):**

Operating Humidity: 20% ~ 80% RH

## Physical Specifications

**Dimensions (W x D x H mm):**

80 x 258.3 mm (3.15" x 10.17")

**Weight (g):**

800

**Color:**

White

## Approval and Compliance

**EMI/EMS:**

CE/FCC

**Safety:**

IK10

**Environmental Test:**

IP66

**Others:**

ONVIF

## Others

**Viewing Systems:**

Microsoft Internet Explorer 8.0 or newer (full functionality)

---

## Order Information

FCS-5102

---

## Package Contents

FCS-5102

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Screw Kit

No liability or responsibility for any errors or omissions in the content.  
Specifications are subject to change without notice.  
All mentioned brand names are registered trademarks and property of their owners.  
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.