



FCS-3098 Version: 1

Fixed Dome IP Network Camera, 8-Megapixel, H.265/264, 4.3X Optical Zoom, 802.3af PoE, IR LEDs, two-way audio, Indoor/Outdoor, Vandalproof

The LevelOne FCS-3098 Fixed Dome Outdoor Camera offers a highly reliable, cost-effective outdoor IP surveillance solution in a low-profile dome mounted casing, which is rated at IP67 and able to withstand outdoor operating conditions such as rain, snow, extreme heat, dust and humidity. The FCS-3098 offers 8-Megapixel resolution, and with 802.3af standard PoE, can use a single Cat.5 cable to run both power and data, making deployments easy and flexible. The dome mounting prevents malicious tampering with the camera, making it a secure and smart choice for all outdoor installations.

Key Features

- 8-Megapixel high-definition resolution
- Video compression: H.264/H.265
- Supports 4.3X optical zoom
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Vandal-proof IK10-rated housing
- Weatherproof IP67-rated housing
- Built-in infrared LEDs for night viewing up to 30m
- Built-in Micro SDHC/SDXC card slot for local storage

Specifications

System Specifications

Standards & Protocols:

TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6

Image Sensor:

1/2.5" Progressive Scan CMOS

Lens:

2.8~12mm motorized VF lens, F2.0

Port:

1 x RJ-45 10/100 Mbps Base-T PoE port

Power Connector

Audio: In/Out

1Vp-p composite output (75 Ω/BNC)

I/O terminal block (1 DI/1 DO)

1 x MicroSDHC/ MicroSDXC card slot

**Button/Knob:**

Reset Button

Indicator:

Power

IR Cut Filter:

Removable infrared-cut filter for day & night function

IR LED:

IR LEDs for illumination up to 30m

Shutter Time:

1/3 ~ 1/100,000 sec

Angle of View:

Horizontal field of view: 115° to 35°

Vertical field of view: 60° to 19°

Diagonal field of view: 146° to 38.5°

Pan/Tilt/Zoom:

4.3X Optical Zoom

Video Compression:

H.265, H.264

Resolution:

50Hz: 20 fps (3840 × 2160), 25 fps (2944 × 1656, 2560 × 1440, 1920 × 1080, 1280 × 720)

60Hz: 20 fps (3840 × 2160), 30 fps (2944 × 1656, 2560 × 1440, 1920 × 1080, 1280 × 720)

Video Format:

AVI

Audio Compression:

G722.1/G711ulaw/G711alaw/G726/MP2L2

Power Input:

12 VDC, 0.95A, max. 11.5W

PoE (802.3af, 37V to 57V), 0.3A to 0.1A, max. 12.9W

Power Consumption:

11.5-12.9W

Data Transfer Rate:

Video Bit Rate: 32 Kbps to 16 Mbps

Audio Bit Rate: 32 to 128kbps

Features

General:

rotate mode. Brightness, contrast, saturation, and sharpness are adjustable via web browser, Motion Detection

PoE:

PoE(802.3af, class 3)

Security:

One-key Reset, Anti-Flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter

Management:

Behavior Analysis: Line crossing detection, intrusion detection, unattended baggage detection, object removal detection

Line Crossing Detection: Cross a pre-defined virtual line, up to 1 pre-defined virtual lines supported

Intrusion Detection: Enter and loiter in a pre-defined virtual region, up to 1 pre-defined virtual regions supported

Object Removal Detection: Objects removed from the pre-defined region, such as the exhibits on display.

Unattended Baggage Detection: Objects left over in the pre-defined region such as the baggage, purse, dangerous materials

Face Detection: Human face appears in the image can be detected and trigger linkage method.

Video:

120dB Wide Dynamic Range

Support 1 fixed region for mainstream and sub stream separately

Audio:

1 audio input (line in), 1 audio output

Performance

Number of Clients:

32

Storage Capacity:

Built-in microSD/SDHC/SDXC slot, up to 128 GB

Frame Rate (fps):

50Hz: 20 fps (3840 × 2160), 25 fps (2944 × 1656, 2560 × 1440, 1920 × 1080, 1280 × 720)

60Hz: 20 fps (3840 × 2160), 30 fps (2944 × 1656, 2560 × 1440, 1920 × 1080, 1280 × 720)

Minimum illumination:

Color: 0.01 lux @(F1.2, AGC ON), 0 lux with IR

Environment

Temperature (°C):

-30 °C to +60 °C (-22 °F to +140 °F)

Humidity (Non-condensing):

Humidity 95% or less

Physical Specifications

Dimensions (W x D x H mm):

153.4 × 153.4 × 133.1 mm (6.04" × 5.24")

Weight (g):

1287

Color:

White

Approval and Compliance

EMI/EMS:

CF/FCC

Safety:

IK10

Environmental Test:

IP67

Others:

ONVIF

Others

Viewing Systems:

IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+

Compatibility:

ISO-9001 certified factory



Order Information

FCS-3098

Package Contents

FCS-3098

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Screw Kit

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.