



FCS-5201 Version: 1

GEMINI Fixed IP Network Camera, 2-Megapixel, H.265, 802.3af PoE, IR LEDs, Indoor/Outdoor

The LevelOne FCS-5201 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 2-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5201 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Key Features

- 2-Megapixel (1920 x 1080) high-definition resolution
- Video compression: H.264, H.265, MJPEG
- IEEE 802.3af PoE compliant to simplify deployment and installation
- Supports IPv4/IPv6 network operation
- Removable IR-cut filter for day and night surveillance
- Built-in infrared LEDs for night viewing up to 30m
- Free surveillance and CMS (Central Management System) software packages with 64-channel license

Specifications

System Specifications

Standards:

IEEE 802.3 10-BASE-T, Ethernet

IEEE 802.3u 100-BASE-TX, Fast Ethernet

IEEE 802.3af Power over Ethernet (PoE)

IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS

Image Sensor:

1/2.8" progressive scan CMOS

Lens:

Board lens, Fixed-focal, f=4mm, F2.0

Port:

1 x RJ-45 10/100 Mbps PoE port

1 x Power port



Button/Knob:
Reset Button

Indicator:
Link/ Act

IR Cut Filter:
Removable infrared-cut filter for day & night function

IR LED:
IR LEDs for illumination up to 30m

Shutter Time:
1/3 s to 1/100, 000 s, support slow shutter

Angle of View:
4 mm @F2.2, horizontal field of view 83.6°

Video Format:
H.264, H.265, MJPEG

Resolution:
1920 × 1080

Output Video Format:
52°

Power Input:
12 VDC ± 25%, 5.5 mm coaxial power plug
PoE (802.3af, class 3)

Power Consumption:
12 VDC, 0.4 A, Max: 5 W
PoE: (802.3af, 37 V to 57 V), 0.2 A to 0.13 A, Max: 7 W

Data Rate:
32 Kbps to 8 Mbps

Digital Zoom:
8x

Operating Temperature (°C):
-30 °C to 50 °C (-22 °F to 122 °F)

Operating Humidity (Non-condensing):
95% or less

Features

General:
Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark

Management:
Motion detection, video tampering alarm, illegal login

Video:
Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser
BLC, 3D DNR
Region of Interest:1 fixed region for main stream and sub-stream

Performance

Number of Clients:
Simultaneous Live View:6
Up to 32 users
3 levels: Administrator, Operator, and User

Frame Rate (fps):

Main Stream:

50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720)

60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720)

Sub-stream:

50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)

60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)

Minimum illumination:

1/3 s to 1/100, 000 s

Physical Specifications

Dimensions (W x D x H mm):

Ø 70 mm × 172.7mm (2.7" × 6.8")

Weight (g):

280g

Color:

White

Approval and Compliance

EMI/EMS:

CE/FCC

Safety:

IP67

TVS 2000V lightning protection, surge protection and voltage transient protection

Others:

ONVIF (PROFILE S, PROFILE G), ISAPI

Manufactured in ISO-9001 and ISO-14001 certified factory,

RoHS

Others

Supported Browsers:

IIE7+, Chrome18-42, Firefox5.0+, Safari5.02+

Compatibility:

Win/7/8/10

Order Information

FCS-5201

Package Contents

FCS-5201

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.