

# MD-Series LED-backlit Display 27" | 24"



## Clinical Displays Geared Toward Safety, Comfort

LED



The MD-Series, with a wide viewing angle designed to accommodate sharing by multiple users, promise to bring medical professionals comfort at work. Their flexibility for installation even in compact, hectic surroundings makes it easy to create an efficient workplace. More importantly, medical-grade safety certification justifies their making a core component of shared workspaces in medical settings: receptions, nurses' carts, charting stations, and pharmacies.






### Ergonomic Design

A versatile stand also marks the MD-Series. Medical professionals can enjoy both comfort and convenience while making use of one of these displays: tilting, pivoting, or swiveling it, adjusting its height, or shifting to either portrait or landscape mode as warranted.

### Medical-Grade Safety Certification

In a departure from standard displays, the MD-Series adopt specially designed low-voltage medical-grade power supply to ensure safety, performance, and reliability—three key requirements for any professional medical environment. Compliance with the EN/IEC 60601-1 standard ensures their safe and reliable performance in the medical setting.



### Wide Viewing Angle and Image Clarity

The MD-Series offer a wide (178°) viewing angle and adjustable aspect ratios for different images, and deliver remarkably crisp images of precise colours and consistent brightness regardless of viewing angles. All this contributes to the benefit that doctors and patients can share information and conduct discussion while viewing a display together.

## Features

- EN60601-1 and IEC60601-1 medical certification
- Portrait/landscape mode selectable
- Wide viewing angles for multiple people use
- White and stylish design for medical environment
- Ergonomically designed stand for viewer's comfort and multiple viewing options
- Selectable aspect ratio for ultimate image size
- VESA mounting for flexible installation in medical environments



## Specifications

### MD-27

### MD-24

Panel	Panel Type	LED-Backlit TFT LCD	LED-Backlit TFT LCD
	Panel Size	27.0"	23.8"
Frequency (H/V)	Max. Resolution	FHD 1920 x 1080	FHD 1920 x 1080
	Pixel Pitch	0.2745 mm	0.2445 mm
	Brightness	250 cd/m <sup>2</sup>	250 cd/m <sup>2</sup>
	Contrast Ratio	1,000 : 1	1,000 : 1
	Viewing Angle (H/V)	178°/178°	178°/178°
	Display Colour	16.7 M	16.7 M
	Response Time	5 ms	5 ms
Input	H Freq.	30 kHz – 83 kHz	30 kHz – 83 kHz
	V Freq.	50 Hz – 76 Hz	50 Hz – 76 Hz
Audio	VGA	15-Pin D-Sub	15-Pin D-Sub
	HDMI	HDMI	HDMI
Power	Audio In	1 x stereo audio jack for PC (3.5 mm)	1 x stereo audio jack for PC (3.5 mm)
	Speaker	2 W X 2	2 W X 2
Operating Conditions	Power Supply	External	External
	Power Requirement	DC 12 V	DC 12 V
Storage Conditions	Consumption	<35 W (On) <0.5 W (Stand-by/Off)	<29 W (On) <0.5 W (Stand-by/Off)
	Temperature	0°C ~ 40°C (32°F ~ 104°F)	0°C ~ 40°C (32°F ~ 104°F)
Mounting	Humidity	10%~85% (No condensation)	10%~85% (No condensation)
	VESA FPMPMI	Yes (100 x 100 mm)	Yes (100 x 100 mm)
Stand	Temperature	-25°C ~ 55°C (-13°F ~ 130°F)	-25°C ~ 55°C (-13°F ~ 130°F)
	Humidity	5%~93% (No condensation)	5%~93% (No condensation)
	Tilt Capacity	-3° ~ 21.5°	-3° ~ 21.5°
	Pivot Capacity	0° ~ 90°	0° ~ 90°
Security	Swivel	±150°	±150°
	Height Adjustment	0-110 mm	0-110 mm
Dimensions	Kensington Security Socket	Yes	Yes
	w/ base (W x H x D)	612.0 x 519.0 x 249.0 mm (24.1" x 20.4" x 9.8")	541.0 x 560.0 x 249.0 mm (21.3" x 22.0" x 9.8")
Weight	Packaging (W x H x D)	715.0 x 450.0 x 305.0 mm (28.1" x 17.7" x 12.0")	632.0 x 417.0 x 282.0 mm (24.9" x 16.4" x 11.1")
	w/o base	6.6 kg (14.6 lb)	5.7 kg (12.6 lb)
Regulation Approval	Packaging	8.9 kg (19.6 lb)	7.8 kg (17.2 lb)
	Certification & Compliance	CE, EN60601-1, IEC60601-1, RoHs, WEEE, REACH	CE, EN60601-1, IEC60601-1, RoHs, WEEE, REACH
Optional Accessories	Accessories	Supplied	Supplied
	Supplied	Power Cord, Power Adaptor, 15-Pin D-sub Cable, Audio Cable, Quick Start Guide, Warranty Card	Power Cord, Power Adaptor, 15-Pin D-sub Cable, Audio Cable, Quick Start Guide, Warranty Card
Optional Accessories	Supplied	Power Cord, Power Adaptor, 15-Pin D-sub Cable, Audio Cable, Quick Start Guide, Warranty Card	Power Cord, Power Adaptor, 15-Pin D-sub Cable, Audio Cable, Quick Start Guide, Warranty Card
	Optional Accessories	Wall Mount: Wall Mounting Arm: WMA-01 Wall Mounting Kit: WMK-01, WMK-03 Ceiling Mount: CMP-01 Desk Mount: Desk Mounting Kit: DMC-01, DMC-02D Desk Mounting Stand: DMS-01D, DMS-01Q Height Adjustable Stand: ES-02	Wall Mount: Wall Mounting Arm: WMA-01 Wall Mounting Kit: WMK-01, WMK-03 Ceiling Mount: CMP-01 Desk Mount: Desk Mounting Kit: DMC-01, DMC-02D Desk Mounting Stand: DMS-01D, DMS-01Q Height Adjustable Stand: ES-02

**Global Headquarters**

Taipei, Taiwan

**EMEA Regional Headquarters**

Capelle a/d IJssel, The Netherlands

**North & South America Regional Headquarters**

San Jose, CA, U.S.A.

**Asia-Pacific Regional Headquarters**

Taipei, Taiwan

**Canada Sales Office**

Vancouver, B.C., Canada

**China Sales Office**

Shanghai, China

**Czech Republic Sales Office**

Brno, Czech Republic

**Denmark Sales Office**

Stoevring, Denmark

**Germany Sales Office**

Mechernich, Germany

**Italy Sales Office**

Livorno, Italy

**Spain Sales Office**

Barcelona, Spain

**Ukraine Sales Office**

Lviv, Ukraine

[www.agneovo.com](http://www.agneovo.com)