# **QuickSpecs**

Overview

### Models

Logitech® QuickCam® Pro 9000 USB Camera, Omni Directional USB Powered Speakers and Desktop Microphone

WF819AA

### Introduction

The HP SkyRoom Standard Accessory Kit combines a high performance webcam, USB powered speakers and a desktop microphone in a single package to complement the HP SkyRoom solution to ensure a life-like visual collaboration experience. This kit enables two or more users at a single site to participate in a SkyRoom session. Whether you are in a small conference room or an office like setting, this SkyRoom accessory kit provides audio/video components needed to get started with visual collaboration.

The high performance webcam offers extreme clarity during a video conference and supports a wide range of video resolutions from 320x240 (30fps) to high def at 720x960(15fps). This webcam also supports 24 bit true color ensuring a vivid and true to life collaboration experience. Designed with an advanced lighting compensation feature, the webcam can optimize the video image in low light conditions and when there is a lot of backlight. Users do not have to manually adjust the focus when conferencing at various distances from the camera because of the embedded autofocus feature. The webcam comes with a universal monitor clip and a 6 foot USB cable for ease of placement.

The HP USB Powered Speakers features omni-directional acoustics which provide consistent terrific sound from anywhere in a room or office. When used during a HP SkyRoom collaboration session, the audio fidelity and clarity projected through the HP USB powered speakers ensure a natural conversing experience. The speakers are extremely attractive and can complement a modern looking desktop setup.

The desktop microphone is a unidirectional microphone that has excellent sound pickup. It features over a 10 foot long cable for added flexibility and mobility.

## **Key Benefits**

### Webcam

- Carl Zeiss® Optics offers high image quality and clarity
- Advanced autofocus supports a range of distances, even close ups and ensures sharp images
- High resolution video that supports video resolutions up to 720x960 pixels at 15 fps guarantees a life-like experience
- Advanced lighting technology optimizes video image even in suboptimal lighting conditions
- Digital Pan Tilt and Zoom, Manual Tilt
- Universal monitor mount

#### **Omni-Directional USB Powered Speakers**

- Listen to music, video or voice collaboration session from anywhere in the room with Omni-directional acoustic technology
- Powered via USB reduces cable clutter
- Sleek design with minimal desktop footprint

#### Desktop microphone

- Unidirectional sound pickup
- Long cable offers microphone placement flexibility



# **QuickSpecs**

Overview

## Compatibility

The HP standard accessory kit is compatible with HP Z200, Z400, Z600, Z800, xw4600 and any HP workstation, HP desktop business PC and notebook that meet the minimum system requirements. Other vendor platforms that meet the minimum system requirements are also supported.

## Service and Support

Your Option Limited Warranty is a one (1) year (HP Option Limited Warranty Period) parts replacement warranty on any HP-branded or Compaq-branded options (HP Options). If your HP Option is installed in an HP Hardware Product, HP may provide warranty service either for the HP Option Limited Warranty Period or the remaining Limited Warranty Period of the HP Hardware Product in which the HP Option is being installed, whichever period is the longer but not to exceed three (3) years from the date you purchased the HP Option.



# **QuickSpecs**

## Technical Specifications

HP SkyRoom Webcam + Desktop Components Audio Kit

SkyRoom

System requirements Windows® 7 or Windows Vista™ Intel® Core 2 Duo 2.3 GHz or higher

Available analog microphone jacks

Kit Contents

Webcam

 USB Powered Speakers Unidirectional microphone

Software and Documentation CD-ROM Product and warranty documentation

**Speakers** 

Frequency response

80Hz - 20kHz, +/-10dB

**Dimensions**  $(H \times W \times D)$ 

90.4 x 90.4 x 252.2 mm (10.94 x 8.11 x 5.28 in.)per speaker

Net weight 648g (1.43 lbs) USB cable length 200 cm (6.6 ft) Speaker cable length 122 cm (4 ft)

Frequency Response 110 Hz to 15000 Hz

Microphone

 $-35 \text{ dBV/}\mu\text{bar}$ , -32 dBV/Pa + / - 3 dBInput sensitivity

Cable

294.2 cm (9.6 ft) shielded plug with a 3.5 mm analog plug

**Dimensions** 

17.2 x 68.5 x 88 mm (0.68 x 2.7 x 3.54 in)

 $(H \times W \times D)$ 

Webcam

 Video – Up to 30 fps VGA Lens – Carl Zeiss Lens • Color Depth – 24 bit

USB 2.0 Interface with Cable – 6 feet

Regulatory

UL/cUL; TUV/(Europe only); NOM (Mexico) **Product Safety EMC** FCC; CE; VCCI; RRL; C-Tick; BSMI; GOST

CE Mark EN 55022:1998; EN 50024

**Telecom** All local telecom requirements and approvals for intended

**USA** 

FCC Part 15 Equipment Certificate; CFR 47, Part 15; other

local requirements

© Copyright 2010 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

Microsoft and Windows are US registered trademarks of Microsoft Corporation.

Intel and Core are registered trademarks of Intel Corporation.

QuickCam and Logicool are a US registered trademarks of Logitech Corporation.

Carl Zeiss is a US registered trademark of Carl Zeiss AG.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

