



FCS-3406 Version: 1

GEMINI Fixed Dome IP Network Camera, 2-Megapixel, H.265, 60fps HFR, 4.3X Optical Zoom, IR LEDs, Indoor/Outdoor

The LevelOne FCS-3406 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 2-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-3406 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Key Features

- 60 fps High Frame Rate (HFR) video in 1080p
- Video compression: H.264, H.265
- Supports 4.3X optical zoom
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Vandal-proof IK10-rated housing
- Weatherproof IP67-rated housing
- Built-in infrared LEDs for night viewing up to 30m
- Built-in Micro SDHC/SDXC card slot for local storage

Specifications

System Specifications

Standards:

TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

Image Sensor:

1/1.8" Progressive Scan CMOS

Lens:

2.8 to 12 mm motorization

Port:

10/100Mbps (100Base-T) RJ45 Ethernet interface

Power Connector

Audio:In/Out

I/O terminal block (1 DI/1 DO)

1 x MicroSDHC/ MicroSDXC card slot

1 RS-485 interface

**Button/Knob:**

Reset Button

IR Cut Filter:

Support

IR LED:

Up to 30m

Shutter Time:

1 s to 1/100,000 s

Angle of View:

Horizontal field of view: 103°to 38°

Vertical field of view: 54°to 21°

Diagonal field of view: 124°to 44°

Video Format:

H.265/H.264/MJPEG

Resolution:

50Hz: 50fps (1920 × 1080, 1280 × 960, 1280×720)

60Hz: 60fps (1920 × 1080, 1280 × 960, 1280×720)

Output Video Format:

MPEG-4

Audio Compression:

G.711/G.722.1/G.726/MP2L2, 64 Kbps (G.711)/16 Kbps

(G.722.1)/16 Kbps (G.726)/32 to 128 Kbps (MP2L2)

Power Input:

12V DC±10%, PoE (802.3af)

Power Consumption:

With extra load: 12 VDC, 0.8 A, max. 10.5 W; PoE (802.3af, 36 V to 57 V), 0.2 A to 0.3 A, class 3

Without extra load: 12 VDC, 0.6 A, max. 8 W; PoE (802.3af, 36 V to 57 V), 0.2 A to 0.3 A, class 3

“with extra load” means that an extra device is connected to and powered by the camera.

Data Rate:

32Kbps~16Mbps

Storage Capacity:

Built-in Micro SD/SDHC/SDXC slot, up to 256 GB

Optical Zoom:

4.3 X

Operating Temperature (°C):

-30 °C ~ 60 °C (-22 °F ~ 140 °F)

Operating Humidity (Non-condensing):

Humidity 95% or less

Mount:

Wall,Ceiling

Features

General:

Motion Detection, Rotated Mode, Mirror, Color Adjustment (Brightness, Contrast, Saturation), Sharpness Adjustment,

Anti-Flicker, Watermark, Privacy Mask,Automatic gain control (AGC) .

PoE:

PoE (802.3af Class3)

Security:

One-key Reset, Heartbeat, Password Protection, IPv4, IPv6, File Management, Object Removal Detection, IP address filtering

Scene change detection, audio exception detection, defocus detection

Management:

Event Triggers (Network Disconnected, IP address Conflict, Illegal Login, HDD Full, HDD Error, Alarm Input, Alarm

Output, Line Crossing Detection, Intrusion Detection, Face detection)

Video:

140 dB Wide Dynamic Range, BLC, Auto White Balance (AWB), 3D DNR, Fifth Stream

Line crossing detection, up to 4 lines configurable

Intrusion detection, up to 4 regions configurable

Region entrance detection, up to 4 regions configurable

Region exiting detection, up to 4 regions configurable

Unattended baggage detection, up to 4 regions configurable

Object removal detection, up to 4 regions configurable

Face detection: detects faces and upload images

Scene change detection, audio exception detection, defocus detection

Audio:

Line IN/Out

8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz

Ease of Use:

Up to 32 users, 3 levels: administrator, operator and user

Performance

Number of Clients:

Live View: Up to 20 channels

Frame Rate (fps):

Main Stream:

50Hz: 50fps (1920 × 1080, 1280 × 960, 1280 × 720)

60Hz: 60fps (1920 × 1080, 1280 × 960, 1280 × 720)

Sub Stream:

50Hz: 25fps (704 × 576, 640 × 480)

60Hz: 30fps (704 × 480, 640 × 480)

Third Stream:

50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480)

60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480)

Fourth Stream:

50Hz: 25fps (1920 × 1080, 1280 × 720, 704 × 576, 640 × 480)

60Hz: 30fps (1920 × 1080, 1280 × 720, 704 × 480, 640 × 480)

Fifth Stream:

50Hz: 25fps (704 × 576, 640 × 480)

60Hz: 30fps (704 × 480, 640 × 480)

Minimum illumination:

Color: 0.002 Lux @ (F1.2, AGC ON)

0 Lux with IR

Physical Specifications

Dimensions (W x D x H mm):

140.5 × 122.6 mm (?5.5? × 4.8?)

Weight (g):

900 g (1.98 lb.)



Color:
White

Approval and Compliance

EMI/EMS:
CE/FCC/UL

Safety:
IK10

Environmental Test:
IP67

Others:
Manufactured in ISO-9001 and ISO-14001 certified factory
RoHS

Others

Supported Browsers:
IE8+

Compatibility:
ONVIF

Order Information

FCS-3406

Package Contents

FCS-3406
Screw Kit
Resource CD (User Manual, Utility, 64-CH Monitoring Software)

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.