

Overview

Models

HP 4510-48G Switch

JF428A

Key features

- Enterprise-class security features
- Wire-speed switching capacity up to 176 Gbps
- Dual-personality copper/fiber ports
- Single IP address management
- IEEE 802.1X network access control

Product overview

The HP 4510G Switch Series provides advanced Gigabit Ethernet access and distribution for medium-sized businesses and smaller enterprise organizations seeking to build a secure converged network. HP 4510G switches support security, and management features, and accommodate up to four optional 10 GbE high-speed links, enabling connectivity to a core network or high-performance servers. The combination of high-performance Gigabit Ethernet switching, quality of service (QoS), and traffic management features help ensure that essential applications receive appropriate priority for efficient utilization of network resources. The series also offers single address management.

Features and benefits

Quality of Service (QoS)

- **Layer 4 prioritization:** enables prioritization based on TCP/UDP port numbers
- **Traffic prioritization (IEEE 802.1p):** allows real-time traffic classification into eight priority levels mapped to eight queues
- **Class of Service (CoS):** sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServ
- **Rate limiting:** sets per-port ingress enforced maximums and per-port, per-queue guaranteed minimums
- **Bandwidth shaping:**
 - Rate limiting: provides per-port, ingress-based enforced bandwidth maximums
 - Guaranteed minimums: provides per-port, per-queue egress-based guaranteed bandwidth minimums
- **Broadcast control:** allows limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic

Management

- **Remote configuration and management:** is available through a secure Web browser or a command-line interface (CLI)
- **Manager and operator privilege levels:** enable read-only (operator) and read-write (manager) access on CLI and Web browser management interfaces
- **Management VLAN:** segments traffic to and from management interfaces, including CLI/telnet, a Web browser interface, and SNMP
- **RADIUS accounting support:** separates RADIUS accounting server support per SSID; provides detailed session, usage, and billing information for each client activity
- **Multiple configuration files:** can be stored to the flash image
- **Dual flash images:** provide independent primary and secondary operating system files for backup while upgrading
- **Secure Web GUI:** provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- **Command-line interface (CLI):** provides a secure, easy-to-use command-line interface for configuring the module via SSH or a

Overview

- switch console; provides direct real-time session visibility
- **SNMPv1, v2c, and v3:** facilitate centralized discovery, monitoring, and secure management of networking devices
- **Port mirroring:** enables traffic on a port to be simultaneously sent to a network analyzer for monitoring
- **3Com-heritage Comware Operating System:** CLI and Web user interface in common with HP E4xxx and E55xxx series switches

Connectivity

- **Auto-MDIX:** automatically adjusts for straight-through or crossover cables on all 10/100 and 10/100/1000 ports
- **Dual-personality functionality:** includes four 10/100/1000 ports or SFP slots for optional fiber connectivity such as Gigabit-SX, -LX, and -LH, or 100-FX
- **IEEE 802.3af Power over Ethernet (PoE):** provides up to 15.4 W per port to IEEE 802.3af-compliant PoE-powered devices such as IP phones, wireless access points, and security cameras
- **Optional 10 GbE ports:** through the use of optional modules, additional 10 GbE connections are available for uplinks or high-bandwidth server connections; flexibly supports XFP, SFP+, or CX4 local connections

Manageability

- **RMON (remote monitoring):** provides advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- **Dual flash images:** provides independent primary and secondary operating system files for backup while upgrading
- **Full-featured console:** provides complete control of the switch with a familiar command-line interface (CLI)
- **Web interface:** allows configuration of the switch from any Web browser on the network
- **Multiple configuration files:** allow multiple configuration files to be stored to a flash image
- **Software updates:** free downloads from the Web
- **sFlow (RFC 3176):** wire-speed traffic accounting and monitoring
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP):** automated device discovery protocol provides easy mapping using network management applications

Layer 2 switching

- **VLAN support and tagging:** support IEEE 802.1Q with 4,094 simultaneous VLAN IDs
- **GARP VLAN Registration Protocol:** allows automatic learning and dynamic assignment of VLANs
- **IP multicast snooping and data-driven IGMP:** automatically prevents flooding of IP multicast traffic
- **Jumbo packet support:** supports up to 9220-byte frame size to improve the performance of large data transfers
- **IEEE 802.1ad QinQ:** increases the scalability of an Ethernet network by providing a hierarchical structure; connects multiple LANs on a high-speed campus or metro network

Layer 3 routing

- **Static IP routing:** provides manually configured routing; includes ECMP capability
- **Routing Information Protocol (RIP):** provides RIPv1 and RIPv2 routing

Security

- **Access control lists (ACLs):** provide IP Layer 3 filtering based on source/destination IP address/subnet and source/destination TCP/UDP port number
- **RADIUS/TACACS+:** eases switch management security administration by using a password authentication server
- **Secure Shell:** encrypts all transmitted data for secure remote CLI access over IP networks
- **Secure Web management with HTTPS and SSL:** encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **IEEE 802.1X and RADIUS network logins:** control port-based access for authentication and accountability

Overview

- **Port security:** allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **MAC address lockout:** prevents particular configured MAC addresses from connecting to the network
- **Secure FTP:** allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of a switch configuration file
- **Switch management logon security:** can require either RADIUS or TACACS+ authentication for secure switch CLI logon
- **Secure management access:** securely encrypts all access methods (CLI, GUI, or MIB) through SSHv2, SSL, and/or SNMPv3
- **Custom banner:** displays security policy when users log in to the switch
- **Automatic VLAN assignment:** automatically assigns users to the appropriate VLAN based on their identity and location and the time of day
- **Management password:** provides security so that only authorized access to the Web browser interface is allowed
- **STP BPDU port protection:** blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- **Dynamic IP lockdown:** works with DHCP protection to block traffic from unauthorized hosts, preventing IP source address spoofing
- **DHCP protection:** blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- **Dynamic ARP protection:** blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- **STP Root Guard:** protects the root bridge from malicious attacks or configuration mistakes

Convergence

- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP):** is an automated device discovery protocol that provides easy mapping of network management applications
- **Automated voice VLAN assignment:** recognizes IP phones and automatically assigns voice traffic to a dedicated VLAN for IP phones

Warranty and support

- **Lifetime warranty:** for as long as you own the product with advance replacement and next-business-day delivery (available in most countries)†
- **Electronic and telephone support:** limited electronic and telephone support is available from HP; to reach our support centers, refer to www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary
- **Software releases:** to find software for your product, refer to www.hp.com/networking/support; for details on the software releases available with your product purchase, refer to www.hp.com/networking/warrantysummary

†HP warranty includes repair or replacement of hardware for as long as you own the product, with next business day advance replacement (available in most countries). The disk drive included with HP AllianceOne Advanced Services and Services zL Modules, HP Threat Management Services zL Module, HP AllianceOne Extended zL Module with Riverbed Steelhead, HP MSM765zL Mobility Controller and HP Survivable Branch Communication zL Module powered by Microsoft Lync has a five-year hardware warranty. For details, refer to the Software license and hardware warranty statements at www.hp.com/networking/warranty.

Technical Specifications

HP 4510-48G Switch (JF428A)

Ports	2 open module slots 44 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 4 SFP dual-personality 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)										
Physical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Dimensions</td> <td>16.54(d) x 17.32(w) x 1.72(h) in. (42.0 x 44.0 x 4.37 cm) (1U height)</td> </tr> <tr> <td style="vertical-align: top;">Weight</td> <td>11.02 lb. (5 kg)</td> </tr> </table>	Dimensions	16.54(d) x 17.32(w) x 1.72(h) in. (42.0 x 44.0 x 4.37 cm) (1U height)	Weight	11.02 lb. (5 kg)						
Dimensions	16.54(d) x 17.32(w) x 1.72(h) in. (42.0 x 44.0 x 4.37 cm) (1U height)										
Weight	11.02 lb. (5 kg)										
Memory and processor	<table border="0"> <tr> <td style="vertical-align: top;">Processor</td> <td>Power PC @ 200 MHz, 16 MB flash, 128 MB SDRAM; packet buffer size: 4 MB shared packet buffer</td> </tr> </table>	Processor	Power PC @ 200 MHz, 16 MB flash, 128 MB SDRAM; packet buffer size: 4 MB shared packet buffer								
Processor	Power PC @ 200 MHz, 16 MB flash, 128 MB SDRAM; packet buffer size: 4 MB shared packet buffer										
Performance	<table border="0"> <tr> <td style="vertical-align: top;">1000 Mb Latency</td> <td>< 3.2 μs</td> </tr> <tr> <td style="vertical-align: top;">10 Gbps Latency</td> <td>< 2.6 μs</td> </tr> <tr> <td style="vertical-align: top;">Throughput</td> <td>131 million pps</td> </tr> <tr> <td style="vertical-align: top;">Switching capacity</td> <td>176 Gbps</td> </tr> <tr> <td style="vertical-align: top;">MAC address table size</td> <td>16000 entries</td> </tr> </table>	1000 Mb Latency	< 3.2 μ s	10 Gbps Latency	< 2.6 μ s	Throughput	131 million pps	Switching capacity	176 Gbps	MAC address table size	16000 entries
1000 Mb Latency	< 3.2 μ s										
10 Gbps Latency	< 2.6 μ s										
Throughput	131 million pps										
Switching capacity	176 Gbps										
MAC address table size	16000 entries										
Reliability	<table border="0"> <tr> <td style="vertical-align: top;">MTBF (years)</td> <td>14.9</td> </tr> </table>	MTBF (years)	14.9								
MTBF (years)	14.9										
Environment	<table border="0"> <tr> <td style="vertical-align: top;">Operating temperature</td> <td>32°F to 113°F (0°C to 45°C)</td> </tr> <tr> <td style="vertical-align: top;">Operating relative humidity</td> <td>10% to 90%, noncondensing</td> </tr> <tr> <td style="vertical-align: top;">Nonoperating/Storage temperature</td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td style="vertical-align: top;">Nonoperating/Storage relative humidity</td> <td>5% to 95%, noncondensing</td> </tr> </table>	Operating temperature	32°F to 113°F (0°C to 45°C)	Operating relative humidity	10% to 90%, noncondensing	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	Nonoperating/Storage relative humidity	5% to 95%, noncondensing		
Operating temperature	32°F to 113°F (0°C to 45°C)										
Operating relative humidity	10% to 90%, noncondensing										
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)										
Nonoperating/Storage relative humidity	5% to 95%, noncondensing										
Electrical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Voltage</td> <td>100-240 VAC</td> </tr> <tr> <td style="vertical-align: top;">Maximum power rating</td> <td>120 W</td> </tr> <tr> <td style="vertical-align: top;">Notes</td> <td>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</td> </tr> </table>	Voltage	100-240 VAC	Maximum power rating	120 W	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.				
Voltage	100-240 VAC										
Maximum power rating	120 W										
Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.										
Safety	IEC 60950-1; EN 60950; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03										
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55022; EN 55024; ICES-003 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6										
Management	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); SNMP Manager; Telnet										
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (UV834E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UV837E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UV840E) 3-year, 24x7 SW phone support, software updates (UV843E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR668E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR669E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR670E)										

Technical Specifications

- 4-year, 4-hour onsite, 13x5 coverage for hardware (UV835E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UV838E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV841E)
- 4-year, 24x7 SW phone support, software updates (UV844E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UV836E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UV839E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV842E)
- 5-year, 24x7 SW phone support, software updates (UV845E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW434E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW435E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW436E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR672E)
- 1-year, 24x7 software phone support, software updates (HR671E)
- 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS714E)
- 1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS715E)
- 3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS716E)
- 3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS717E)
- 4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS718E)
- 4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS719E)
- 5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS720E)
- 5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS721E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

(applies to all products in series)

General protocols

- IEEE 802.1ag Service Layer OAM
- IEEE 802.1D MAC Bridges
- IEEE 802.1p Priority
- IEEE 802.1Q (GVRP)
- IEEE 802.1s Multiple Spanning Trees
- IEEE 802.1v VLAN classification by Protocol and Port
- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
- IEEE 802.1X PAE
- IEEE 802.3ad Link Aggregation (LAG)
- IEEE 802.3ae 10-Gigabit Ethernet
- IEEE 802.3x Flow Control
- RFC 768 UDP
- RFC 792 ICMP
- RFC 793 TCP
- RFC 826 ARP
- RFC 854 TELNET
- RFC 925 Multi-LAN Address Resolution

MIBs

- IEEE 8021-PAE-MIB
- IEEE 8023-LAG-MIB
- RFC 1213 MIB II
- RFC 1493 Bridge MIB
- RFC 1724 RIPv2 MIB
- RFC 2011 SNMPv2 MIB for IP
- RFC 2013 SNMPv2 MIB for UDP
- RFC 2233 Interface MIB
- RFC 2452 IPV6-TCP-MIB
- RFC 2454 IPV6-UDP-MIB
- RFC 2465 IPv6 MIB
- RFC 2466 ICMPv6 MIB
- RFC 2571 SNMP Framework MIB
- RFC 2572 SNMP-MPD MIB
- RFC 2573 SNMP-Notification MIB
- RFC 2573 SNMP-Target MIB
- RFC 2665 Ethernet-Like-MIB
- RFC 2819 RMON MIB
- RFC 2925 Ping MIB

Technical Specifications

RFC 951 BOOTP
RFC 1058 RIPv1
RFC 1350 TFTP Protocol (revision 2)
RFC 1519 CIDR
RFC 1542 Clarifications and Extensions for the Bootstrap Protocol
RFC 2131 DHCP
RFC 2453 RIPv2
RFC 3046 DHCP Relay Agent Information Option
RFC 3576 Ext to RADIUS (CoA only)
RFC 4675 RADIUS VLAN & Priority

IPv6

RFC 2080 RIPng for IPv6
RFC 2460 IPv6 Specification
RFC 2710 Multicast Listener Discovery (MLD) for IPv6
RFC 2740 OSPFv3 for IPv6
RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only)
RFC 3019 MLDv1 MIB
RFC 3162 RADIUS and IPv6
RFC 3315 DHCPv6 (client and relay)
RFC 3513 IPv6 Addressing Architecture
RFC 3810 MLDv2 (host joins only)
RFC 4022 MIB for TCP
RFC 4251 SSHv6 Architecture
RFC 4252 SSHv6 Authentication
RFC 4253 SSHv6 Transport Layer
RFC 4254 SSHv6 Connection
RFC 4293 MIB for IP
RFC 4419 Key Exchange for SSH
RFC 4443 ICMPv6
RFC 4541 IGMP & MLD Snooping Switch
RFC 4861 IPv6 Neighbor Discovery
RFC 4862 IPv6 Stateless Address Auto-configuration

RFC 3414 SNMP-User based-SM MIB
RFC 3415 SNMP-View based-ACM MIB
RFC 3418 MIB for SNMPv3
RFC 3826 AES for SNMP's USM MIB
RFC 4133 Entity MIB (Version 3)
LLDP-EXT-DOT1-MIB
LLDP-EXT-DOT3-MIB
LLDP-MIB

Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)
RFC 3176 sFlow
ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)
SNMPv1/v2c/v3

Security

IEEE 802.1X Port Based Network Access Control
RFC 1492 TACACS+
RFC 2865 RADIUS Authentication
RFC 2866 RADIUS Accounting
Secure Sockets Layer (SSL)
SSHv2 Secure Shell

Accessories

HP 4510G Switch Series accessories

Modules

HP 4500/4800 1-port 10GbE XFP Module	JE053A
HP 4500/4800 2-port 10GbE XFP Module	JE049A
HP 5500/5120 2-port 10GbE SFP+ Module	JD368B
HP 4500/4800 2-port 10GbE LCM Module	JE051A
HP 5500 2-port 10GbE Local Connect Module	JD360B

Transceivers

HP X110 100M SFP LC FX Dual Mode Transceiver	JD497A
HP X110 100M SFP LC LX Dual Mode Transceiver	JD498A
HP X120 1G SFP RJ45 T Transceiver	JD089B
HP X124 1G SFP LC SX Transceiver	JD493A
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X130 SC LR XFP Transceiver	JD108B
HP X130 LC SR XFP Transceiver	JD117B
HP X135 LC ER XFP Transceiver	JD121A
HP X130 CX4 XFP Transceiver	JD506A
HP X130 SFP+ LC SR Transceiver	JD092B
HP X130 SFP+ LC LRM Transceiver	JD093B
HP X130 SFP+ LC LR Transceiver	JD094B
HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable	JD095C
HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable	JD096C
HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	JD097C

Cables

HP 50 cm CX4 Cable	JE054A
HP 100 cm CX4 Cable	JE055A
HP 300 cm CX4 Cable	JE056A
HP 0.5 m Multimode OM3 LC/LC Optical Cable	AJ833A
HP 1 m Multimode OM3 LC/LC Optical Cable	AJ834A
HP 2 m Multimode OM3 LC/LC Optical Cable	AJ835A
HP 5 m Multimode OM3 LC/LC Optical Cable	AJ836A
HP 15 m Multimode OM3 LC/LC Optical Cable	AJ837A
HP 30 m Multimode OM3 LC/LC Optical Cable	AJ838A
HP 50 m Multimode OM3 LC/LC Optical Cable	AJ839A
HP X230 Local Connect 50cm CX4 Cable	JD363B
HP X230 Local Connect 100cm CX4 Cable	JD364B
HP X230 CX4 to CX4 3m Cable	JD365A
HP 4510-48G Switch (JF428A)	
HP 1 m PremierFlex OM3+ LC/LC Optical Cable	BK838A
HP 2 m PremierFlex OM3+ LC/LC Optical Cable	BK839A
HP 5 m PremierFlex OM3+ LC/LC Optical Cable	BK840A
HP 15 m PremierFlex OM3+ LC/LC Optical Cable	BK841A
HP 30 m PremierFlex OM3+ LC/LC Optical Cable	BK842A
HP 50 m PremierFlex OM3+ LC/LC Optical Cable	BK843A

Accessory Product Details

NOTE: Details are not available for all accessories. The following specifications were available at the time of publication.

HP 4500/4800 1-port 10GbE XFP Module (JE053A)	Ports	1 XFP 10-GbE port; Duplex: full only
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 4500/4800 2-port 10GbE XFP Module (JE049A)	Ports	2 XFP 10-GbE ports; Duplex: full only
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 4500/4800 2-port 10GbE LCM Module (JE051A)	Ports	2 CX4 10-GbE ports; Duplex: full only
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X110 100M SFP LC FX Dual Mode Transceiver(JD497A)	Ports	1 LC 100 Mbps port
	Connectivity	Connector type LC
A small form-factor pluggable (SFP) 100 MB/s Dual mode transceiver that provides a full duplex 100Mb/s solution up to 2km on a multi mode fiber.	Physical characteristics	Wavelength 1310 nm
	Electrical characteristics	Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		Full configuration weight 0.04 lb. (0.02 kg)
		Power consumption typical 0.8 W
		Power consumption maximum 1.0 W
Cabling	Cable length	2km
	Fiber type	Multi Mode
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

Accessory Product Details

HP X110 100M SFP LC LX10 Ports Transceiver (JD498A)

A small form-factor pluggable (SFP) 100Mb/s transceiver that provides a full duplex 100Mb/s solution for up to 10km on a single mode cable.

Connectivity	1 LC 100 Mbps port
Connector type	LC
Wavelength	1310 nm
Physical characteristics	Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
Electrical characteristics	Full configuration weight 0.04 lb. (0.02 kg)
	Power consumption typical 0.8 W
	Power consumption maximum 1.0 W
Cabling	Cable length 10km
	Fiber type Single Mode
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X120 1G SFP RJ45 T Transceiver (JD089B)

A small form factor pluggable (SFP) Gigabit 1000Base-T transceiver that provides a full duplex Gigabit solution up to 100m on a Cat-5+ cable.

Ports	1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T)
Connectivity	Connector type RJ-45
Physical characteristics	Dimensions 2.71(d) x 0.54(w) x 0.55(h) in. (6.88 x 1.37 x 1.4 cm)
Electrical characteristics	Full configuration weight 0.07 lb. (0.03 kg)
	Power consumption typical 0.8 W
	Power consumption maximum 1.0 W
Cabling	Cable type: 1000BASE-T: Category 5 (5E or better recommended), 100 Û differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T;
	Maximum distance: • 100m
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP X124 1G SFP LC SX Transceiver (JD493A) JD493A HP X124 1G SFP LC SX Transceiver that provides a full duplex Gigabit solution up to 550m on Multi Mode fiber.	Ports	1 LC 1000BASE-SX port	
	Connectivity	Connector type LC	
	Physical characteristics	Wavelength	850 nm
		Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		Full configuration weight	0.04 lb. (0.02 kg)
	Electrical characteristics	Power consumption typical	0.8 W
		Power consumption maximum	1.0 W
	Cabling	Maximum distance: • 220m-550m Fiber type	Multi Mode
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

HP X125 1G SFP LC LH70 Transceiver (JD063B) A small form-factor pluggable (SFP) Gigabit LH70 transceiver that provides a full-duplex Gigabit solution up to 70km on a single-mode fiber.	Ports	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)	
	Connectivity	Connector type LC	
	Physical characteristics	Wavelength	1550 nm
		Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		Full configuration weight	0.04 lb. (0.02 kg)
	Electrical characteristics	Power consumption typical	0.8 W
		Power consumption maximum	1.0 W
	Cabling	Cable type: Single-mode fiber optic, complying with ITU-T G.652; Maximum distance: • 70km Fiber type	Single Mode
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

Accessory Product Details

HP X130 10G XFP CX4 Transceiver (JD506A) An XFP 10 Gigabit CX4 transceiver that provides full duplex 10G solution using CX4 cabling.	Ports	1 CX4 10-GbE port; Duplex: full only
	Connectivity	Connector type CX4
	Cabling	Cable length 15m Max CX4 cables
	Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)	Cabling	Cable type: 50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m Maximum distance: 10Gbps Transfer Rate (Ethernet): 300m
	Notes	Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end. <ul style="list-style-type: none"> • Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um • Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm. • Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links. • CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows. • BULK CABLE & CABLE ASSEMBLY CONFIGURATION: • Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic. • Jacket Color: Aqua for OM3 multimode per TIA 598 • Boot Color: White • Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters. • Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46. • Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 1 m Multimode OM3 LC/LC Optical Cable
(AJ834A)

Cabling

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 2 m Multimode OM3 LC/LC Optical Cable
(AJ835A)

Cabling

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 5 m Multimode OM3 LC/LC Optical Cable **Cabling**
(AJ836A)

Cable type:

50/125 µm core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: This specification defines the detail requirements for a tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 15 m Multimode OM3 LC/LC Optical Cable **Cabling**
(AJ837A)

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 30 m Multimode OM3 LC/LC Optical Cable **Cabling**
(AJ838A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 50 m Multimode OM3 Cabling
LC/LC Optical Cable
(AJ839A)

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 1 m PremierFlex OM3+ Notes LC/LC Optical Cable (BK838A)

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 2 m PremierFlex OM3+ Notes LC/LC Optical Cable (BK839A)

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 5 m PremierFlex OM3+ Notes
LC/LC Optical Cable
(BK840A)

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 15 m PremierFlex Notes
OM3+ LC/LC Optical Cable
(BK841A)

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP 30 m PremierFlex OM3+ LC/LC Optical Cable (BK842A) **Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 50 m PremierFlex OM3+ LC/LC Optical Cable (BK843A) **Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

To learn more, visit: www.hp.com/networking

© Copyright 2012 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.