

## i-tec USB-C HDMI DP Docking Station with Power Delivery 65W + i-tec Universal Charger 77 W

i-tec USB-C HDMI DP Docking Station with Power Delivery 65W + i-tec Universal Charger 77 W



### PRODUCT DESCRIPTION

USB-C office docking station with support for up to 2 external monitors with 4K resolution. The station is compatible with any laptop equipped with a USB-C or Thunderbolt 3 port. 6x USB ports, reliable and quick connection to your business network thanks to an integrated LAN port and support for installation behind a monitor make the docking station an ideal partner for professionals. And of course, the station is capable of charging your laptop or tablet with up to 65W (charging adapter included). Integrated latest DP 1.4 protocol supports 5K/60 Hz resolution, making the device suitable for even professional graphics designers, data analysts, film editors and, of course, fans of HD video.

The docking station also comes with a [USB-C power adapter](#) with a total power of 77 W (USB-C port: 65 W and 1x USB-A port with a power of 12W)

Note: macOS does not support Multi Stream Transport (MST) technology. Connecting two monitors to the station on macOS will result in both monitors showing the same image.

- Connect up to two 4K/30 Hz external monitors
- Power delivery: up to 65 W ([power adapter](#) with a total power of 77 W is included)
- 1x HDMI, 1x DisplayPort
- 3x USB 3.1, 1x USB-C 3.1 and 2x USB 2.0 for easy connection of your USB devices and peripherals. Gigabit Ethernet RJ-45 provides reliable, robust and high-speed Internet connection supporting 10/100/1000 Mbps speeds
- Combined jack for audio and microphone on the front panel
- Kensington lock protects against theft, particularly in shared offices or public spaces
- On/off switch for maximum energy savings
- The station features VESA support, allowing smart vertical installation behind a VESA compatible monitor
- Supports Windows 10, macOS X, Android, ChromeOS and Linux

### PRODUCT FEATURES

#### DOCKING STATION:

- 1x integrated USB-C cable for connecting to a device (100 cm)
- Docking station technology: [USB-C \(MST\)](#)
- Power Delivery: 65 W
  - Internal power consumption: 5-10W ([more info here](#))
- Video ports: 1x HDMI, 1x DisplayPort ([DP++ support](#))
- [Resolution:](#)

- **Host device with DisplayPort 1.2 support:**
  - 1 monitor – 1x HDMI or DP → up to 4K/30Hz
  - 1 monitor – 1x HDMI or DP → up to 1080p/120Hz
  - 2 monitors – 1x DP + 1x HDMI → up to 2x 1080p/60Hz\*
- **Host device with DisplayPort 1.4 support:**
  - 1 monitor – 1x HDMI or DP → up to 4K/60Hz
  - 1 monitor – 1x HDMI or DP → up to 1440p/144Hz or 1080p/240Hz
  - 2 monitors – 1x DP + 1x HDMI → up to 2x 1440p/60Hz\* or 2x 4K/30Hz\*
- **Host device with DisplayPort 1.4 with DSC support:**
  - 1 monitor – 1x HDMI → up to 4K/60Hz
  - 1 monitor – 1x DP → up to 5K/60Hz
  - 1 monitor – 1x HDMI → up to 1440p/144Hz or 1080p/240Hz
  - 1 monitor – 1x DP → up to 4K/144Hz or 1440p/240Hz or 1080p/360Hz
  - 2 monitors – 1x DP + 1x HDMI → up to 2x 4K/60Hz\*
  - 2 monitors – 1x DP + 1x HDMI → up to 2x 1440p/144Hz\*
- 1x USB-C port Gen. 2 (data only)
- 1x USB-C port gen. 2 + PD (data + power delivery)
- 3x USB 3.0 port
- 2x USB 2.0 port
- 1x Ethernet GLAN RJ-45 port (Realtek AX88179A)
- 1x 3,5 mm Combo Audio port
- LED indication
- ON/OFF switch for the docking station
- Kensington lock support
- VESA support
- OS: Windows 10/11, macOS\*, iPadOS\*\*, Android\*\*, Chrome OS and Linux with latest updates
- Product dimensions: 113 x 113 x 40 mm

#### **CHARGER:**

- Input voltage AC 100-240 V, 50-60 Hz
  - Output power (max.): 77 W
  - USB-C output voltage: DC 5 V / 9 V / 12 V / 15 V / 20 V
  - USB-C output current: max. 3.25 A
  - USB-A output voltage: DC 5V
  - USB-A output current: max. 2.4 A
  - Protection against: Current overload, overvoltage, short circuit and overheating.
  - Operating temperature: 0°C – 40°C
- 
- Package dimensions: 338 x 150 x 55 mm
  - Package weight: 828 g

#### **Hardware Requirements:**

- Device with a free USB-C, USB4 or Thunderbolt™ 3/4 port

#### **Power Delivery Requirements:**

- Device with a free USB-C, USB4 or Thunderbolt™ 3/4 port with Power Delivery support

#### **Video Output Requirements:**

- Device with a free USB-C or USB4 port with DisplayPort Alternate Mode support or a Thunderbolt™ 3/4

port

### Operating System:

- Windows 10 / 11, macOS\*, iPadOS\*\*, Android\*\*, Chrome OS and Linux with latest updates

\* macOS does not support Multi Stream Transport (MST) technology. Connecting two monitors to the station on macOS will result in both monitors showing the same image.

\*\* iPadOS, Android do not support multi-screen video transfer technology, nor the extended screen option. This means that when connected to an external monitor, only the mirrored screen will be displayed. (Not valid for androids with DEX and Easy Projection extension)

## SPECIFICATION

Part Number	Product Description & EAN
C31HDMIDPDOCKPD65	i-tec USB-C HDMI DP Docking Station with Power Delivery 65W + i-tec Universal Charger 77 W EAN: 8595611704772
C31HDMIDPDOCKPD65UK	i-tec USB-C HDMI DP Docking Station with Power Delivery 65W + i-tec Universal Charger 77 W EAN: 8595611704789
<b>Hardware</b>	
Bus type	USB-C, Thunderbolt-3, Thunderbolt-4
<b>Ports/Connectors</b>	
<b>System Requirements</b>	
Operating system	Windows 10/11 macOS X Android Linux Chrome OS R51 or later
<b>Other features</b>	
Colour	black
Housing Material	ABS
Product Dimensions	113 x 113 x 40 mm
Product Weight	245 g
Package Weight	828 g
Packaging Dimensions (LxWxH)	338 x 150 x 55 mm
<b>Support</b>	
Warranty period	2 years
Technical support	lifetime
<b>Package contents</b>	
Product	
Instruction manual	

Universal adapter 77 W

For further information regarding setup or for answers to FAQ's, please visit our website [i-tec.pro](https://www.i-tec.pro).  
Specifications are subject to change without notice.

Updated 10.2.2023