



REV	MODIFICATION	DATE
A		2021.01.12



**A. Electronic Tests:**

- A. Open/Short/Intermittence: 100%
  - B. Hi-Pot: AC 100V 0.01S 1mA
  - C. Insulation Resistance: DC 100V 0.01S 5MΩ Min
  - D. Conductive Resistance: 2Ω Max
- B. USB READ WRITE TEST: (GEN2 1M) : (READ) 300MB/S (min), (WRITE) 500MB/S(min);

⑥	DUST COVER	USB3.1 Male Dust Cap	2	PCS
⑤	Coppr Foil	Double Conducting Copper Foil 5u*5m	40	MM
④	MOLDED	45P Black PVC	5	G
③	CONNECTOR	USB3.2 C TYPE Male, Pin Gold Plated, Shell Nickel Plated, E-MARK(5A)+EMI Shield	1	PCS
②	CONNECTOR	USB3.2 C TYPE Male, Pin Gold Plated, Shell Nickel Plated +EMI Shield	1	PCS
①	CABLE	[1P*32#(7/0.08TC)+D(7/0.08TC)+AL+MY] *4C+1P*32#(7/0.08TC)+4C*32#(7/0.08TC)+20# (61/0.10TC)*1C+D(41/0.08)+F+AL+ B(16*9/0.08TC) Black PVC OD:4.8MM ±0.2 Marking: E***** 兄 AWM STYLE 2725 80°C 30V VW-1 SUPER HIGH SPEED USB Revision 3.1	1500	MM
NO	NAME		Q'TY	UNIT

PROJ:

TOLERANCE: XX= XXX=

PRODUCT NAME: USB3. 2CC1. 5

SCALE: NONE

REV: A

PART NO: 201930073

UNIT: MM

SHEET: 1/3

CUST: EET Group A/S

SUST APPROVED:

APPROVED: Emil Olsen

CHECKED:

DRAWING: 2021.01.12

