



NO	Product name	Model specification	Remarks
1	PE011405	H05VV-F 3G1.5mm ² *0.5M	Black
2	PE011410	H05VV-F 3G1.5mm ² *1.0M	Black
3	PE011415	H05VV-F 3G1.5mm ² *1.5M	Black
4	PE011420	H05VV-F 3G1.5mm ² *2.0M	Black
5	PE011400	H05VV-F 3G1.5mm ² *2.5M	Black
6	PE011403	H05VV-F 3G1.5mm ² *3.0M	Black

Notes:

1. Cable: H05VV-F 3G0.75mm² Jacket $\phi 6.5 \pm 0.1$ Conductor 24*0.198
H05VV-F 3G1.5mm² Jacket $\phi 8.0 \pm 0.2$ Conductor 48*0.198
2. Mark: \triangleleft VDE \triangleright H05VV-F 3G0.75mm²
 \triangleleft VDE \triangleright H05VV-F 3G1.5mm²
3. Test: Hi-pot: Inner Voltage AC2500V/1S External Voltage AC4500V/1S
current leakage 1mA, insulation resistance no less than 50M Ω , no strike out;

5.		ACCORDING	DIN VDE 0620 - 1		MATERIAL	PVC	
4.			IEC60320		RATED	16A 250V ~ /10A 250V ~	
3.	JT-ST3H	DRAWER		EDITION	A4	Dr.No.	
2.	WIRE	REVIEW				COLOR	
1.	JT-SZ3 Plug to the European standard	APPROVE	Zhang	2019-7-8		ALL DIMENSIONS IN mm	
PART	DESCRIPTION	DO NOT SCALE	DATE				