

3 inch Mobile Printer

# MP-B30



- Compact & Light Weight
- Drop rating: 1.8m (6feet), IP rating: IP54
- Printing Speed: 127mm/sec max
- Simple Operation & Stylish Design
- Option Cradle for Charging

UNDER DEVELOPMENT



Model	MP-B30
Method	Thermal line dot printing
Number of dots/line	576
Resolution (dots/mm)	8
Paper width (mm)	80 <sup>+0</sup> <sub>-1</sub>
Printing width (mm)	72
Printing speed (mm/sec) max	127 (5inch)
Outside diameter of paper roll (mm)max	Φ51
Character matrix (HxW dots)	24 × 12, 24 × 24, 16 × 8, 16 × 16
Character dimensions (H×W mm)	3.0 × 1.5, 3.0 × 3.0, 2.0 × 1.0, 2.0 × 2.0
Type of paper	Roll paper
Character type	Code page (17pages), Optional font, Downloaded character, User-defined character, JIS 1&2 Level Kanji, Special character
Barcode	UPC-A/E, JAN (EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128, PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar
Power supply	Li-Ion Battery
Communication interface	USB, Bluetooth®, W-LAN <sup>*1</sup>
Input buffer	4K bate
Command	ESC/POST™ conformity
Cutting method	Tear bar
Falling resistance	1.8m <sup>*2</sup>
IP rating	IP54 <sup>*2</sup>
Operating Temperature (°C)	-20 to 55
Service life: Abrasion resistance (km)	50 <sup>*3</sup>
Dimensions (W×D×Hmm)	105 x 126 x 58 <sup>*4</sup>
Mass (g)	395 <sup>*5</sup>
Standard	FCC, CE, VCCI
Bundled item	AC dapter, Battery, USB cable, Belt crip
Option	Cradle for charging, Single battery charger, Quad battery charger, Cigarette socket charger, Strap
SW	Printer driver, OPOS, POS for .NET, Windows® CE (SDK), Android™ (SDK)

\*1 Selected model. \*2 This number is test result based on SII procedures, not guaranteed value. \*3 Use recommended thermal papers. \*4 Excluding protrusion \*5 with battery, without paper roll

ESC/POST™: Registered trademark of SEIKO EPSON CORP.  
Windows® is the registered trademark of Microsoft Corporation(USA).  
Android™ is a trademark of Google Inc.

Official site <http://www.sii-ps.com>

Printed in Oct. 2018



**Seiko Instruments Inc.**  
Print System Div.  
8, Nakase 1-chome, Mihama-ku  
Chiba-shi, Chiba 261-8507, Japan  
Telephone:+81-43-211-1106 Facsimile:+81-43-211-8037

**Seiko Instruments U.S.A., Inc.**  
21221 S. Western Ave., Suite 250, Torrance, CA 90501, USA.  
Telephone:+1-310-517-7778 Facsimile:+1-310-517-7779

**Seiko Instruments GmbH**  
Siemensstrasse 9 D-63263 Neu-Isenburg, Germany  
Telephone:+49-6102-297-0 Facsimile:+49-6102-297-222  
E-mail : info@seiko-instruments.de

