

MPN: UTP690

CAT6 U/UTP Network Cable 90m, Grey

CAT6a cables is an updated version of CAT6 slim cables. These cables enables a convenient and reliable connection from one network device, such as switch, modem or router, to another or to the infrastructure at large through a patch panel, keystone jack or wall outlet. This cable are also used a lot in offices and home network and entertainment applications. The cables are tested up to 500Mhz / 1000 Mbps (CAT6a standard) and are backwards compatible with CAT6, CAT5e and CAT5 cables. They are produced with latch protection, which prevents the connector do be damaged when you install the cable through an installation with very less space.

- Suitable for Gigabit (10/100/1000 N
- LSZH (Low Smoke Zero Halogen)
- CAT6 tested up to 250 MHZ
- with Latch Protection
- with slimline relief
- with gold-plated pins

Specifications

Features

d version of CAT6 slim cables. These cal nnection from one network device, suc er or to the infrastructure at large thro I outlet. This cable are also used a lot ir inment applications. The cables are te a standard) and are backwards compa es. They are produced with latch prote be damaged when you install the cab pace. 200/1000 Mbit) network Halogen) HZ	ch as switch, ugh a patch n offices and ested up to atible with ection, which
AWG wire size	24
Cable length	90 m
Cable shielding	U/UTP (UTP)
Cable standard	Cat6
Certification	EIA/TIA 568
Conductor material	Copper
Conductor type	Stranded
Connector 1	RJ45
Connector 1 gender	Male
Connector 2	RJ45
Connector 2 gender	Male
Data transfer rate	10000 Mbit/s
Frequency	250 MHz
Halogen-free	Yes
Jacket material	Low smoke zero halogen (LSZH), Polyethylene (PE)

Haloge Jacket Product colour Grey **RoHS** compliance Yes Other features **Product series Round Cable Technical features** Kink Protection, strain relief and Latch Protection Package dimensions Gross Weight (Package, kg) 1.85 kg Packaging data Quantity per pack 1 pc(s) **Product dimensions** Net Weight (Product, kg) 1.75 kg Vendor information **Brand Name** MicroConnect Warranty 25 Year(s)

Please note that specifications are subject to change without prior notice.



Weight & dimensions

Outer diameter

6 mm