

MPN: FIB112001-2

## Optical Fibre Cable, ST-ST, Singlemode, Duplex, OM2 (Orange), 1m

The 50/125µm OM2 multimode fiber optic cable is optically tested for insertion loss to ensure high quality. It is very cost-effective for network cabling in data centers, enterprise networks, telecom rooms, server farms, cloud storage networks, and any place where fiber patch cables are needed. OM2 patch cords are manufactured using LSZH cables and conform to IEC, EIA TIA or Telcordia standards.



- Designed for Data Centers, Industry and Computer Centers
- LSZH (Low Smoke Zero Halogen) and flame retardant
- RoHS compliant

## **Specifications**

Contures	Cable length	1m
Features	-	
	Cladding diameter	125 µm
	Connector 1	ST/UPC
	Connector 1 gender	Male
	Connector 2	ST/UPC
	Connector 2 gender	Male
	Core diameter	50 μm
	Fiber mode structure	Multi-mode
	Fibre optic type	OM2
	Full duplex	Yes
	Halogen-free	Yes
	Insertion loss	0.3 dB
	Jacket material	Low smoke zero halogen (LSZH)
	Product colour	Green
	RoHS compliance	Yes
Operational conditions	Operating temperature (T-T)	-40 - 85 °C
	Storage temperature (T-T)	-40 - 85 °C
Package dimensions	Gross Weight (Package, kg)	0.1 kg
Product dimensions	Net Weight (Product, kg)	0.05 kg
Vendor information	Brand Name	MicroConnect
	Warranty	25 Year(s)
Weight & dimensions	Cable diameter	2 mm



## Other products in this series

Cable length	Multi-mode
0.5	FIB1120005-2
1.0	FIB112001-2
2.0	FIB112002-2
3.0	FIB112003-2
5.0	FIB112005-2
7.0	FIB112007-2
10.0	FIB112010-2
15.0	FIB112015-2
20.0	FIB112020-2
25.0	FIB112025-2