

Mobile Printer

MP-A40 Series

UNDER DEVELOPMENT

Measuring
InstrumentPDA/
Smart Device

Barcode

Portable
Printer

Label

Medical
Equipment

High Reliability

- Drop rating: 2.0m(6.6feet) multiple
- IP rating: IP54
- Operating temperature: -20°C to 50°C

Wide variety of driver and SDK for mobile equipment

Simple operation

Stylish design



Tough & Stylish Mobile Printer
MP-A40
 SERIES

Model	MP-A40
Method	Thermal line dot printing
Number of dots/line	832
Resolution (dots/mm)	8
Paper width (mm)	80 ⁺⁰ ₋₁ / 100 ⁺⁰ ₋₁ / 105 ⁺⁰ ₋₁ / 112 ⁺⁰ ₋₁
Printing width (mm)	104
Speed (mm/sec) max	105
Outside diameter of paper roll (mm) max	Φ 58
Character matrix (HxW mm)	24 x 12, 24 x 24, 16 x 8, 16 x 16
Character dimensions (HxW mm)	3.0 x 1.5, 3.0 x 3.0, 2.0 x 1.0, 2.0 x 2.0
Type of paper	Roll paper, Label roll paper
Character type	Code page : 17pages, Katakana character, Option font, Downloaded character, User-defined character, JIS 1 & 2 level kanji
Bar code	UPC-A/E, JAN(EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128, PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar
Power supply(v)	Option : Specified AC adapter, Li-Ion battery
Communication interface	USB, Bluetooth®, Ethernet*1
Input buffer	4K bytes
Command	ESC/POS™ conformity, CPCL conformity, Markup Language
Cutting	Tea bar
Drop Rating	2.0m (6.6feet) multiple ¹
IP rating	IP54 ¹
Operating temperature (°C)	-20 to 50
Service life (km)	50 ²
Dimensions (WxDxH mm)	156.0 x 152.1 x 71.0 ³
Mass (g)	Approx. 750 ⁴
Standard	FCC, CE, VCCI
Option	AC adapter, Battery pack, Battery charger(single/quad), AC cable, USB cable, Serial cable, Car charger, Strap
Software	Printer driver, Windows® CE(SDK), Android™(SDK)

*1 test performance by specified condition. *2 Use recommended thermal papers. *3 Excluding protrusion *4 Including battery, excluding roll paper

ESC/POS™ is a registered trademark of SEIKO EPSON Corporation.
 Windows® is a registered trademark of Microsoft Corporation(USA).
 Android™ is a trade mark of Google Inc.