

MPN: SSTP650Y

CAT6 S/FTP Network Cable 50m, Yellow

CAT6a cables is an updated version of CAT6 slim cables. These cables enables a convenient and reliable connection from one network device, such as switch, modem or router, to another or to the infrastructure at large through a patch panel, keystone jack or wall outlet. This cable are also used a lot in small office and home network and entertainment applications. The cables are tested up to 500Mhz / 1000 Mbps (CAT6a standard) and are backwards compatible with CAT6, CAT5e and CAT5 cables. They are produced with latch protection, which prevents the connector do be damaged when you install the cable through an installation with very less space. Furthermore these cables are manufactured with shielding. This protects against both EMI (electromagnetic interference). EMI can cause crosstalk between circuits, resulting in degradation of data, increased errors and slower transmission rates, but by using this shielded cable you will avoid this problem.



- S/FTP Shielding, protects against EMI (Electromagnetic interference)LSZH (Low Smoke Zero Halogen)
- CAT6 tested up to 250 MHz
- with latch protection
- with slimline strain relief
- with gold plated PINs

Specifications

Fea	tu	res

Other features

Package dimensions

AWG wire size	28	
Cable length	50 m	
Cable shielding	S/FTP (S-STP)	
Cable standard	Cat6	
Conductor material	Copper	
Conductor type	Stranded	
Connector 1	RJ45	
Connector 1 gender	Male	
Connector 2	RJ45	
Connector 2 gender	Male	
Data transfer rate	10000 Mbit/s	
Frequency	250 MHz	
Halogen-free	Yes	
Jacket material	Low smoke zero halogen (LSZH)	
Product colour	Yellow	
RoHS compliance	Yes	
Twisted pair coupling type	4x2	
Product series	Round Cable	
Technical features	Kink Protection, strain relief and Latch Protection	
Gross Weight (Package, kg)	1.65 kg	



Packaging data	Quantity per pack	1 pc(s)
Product dimensions	Net Weight (Product, kg)	1.54999999999998 kg
Vendor information	Brand Name	MicroConnect
	Warranty	25 Year(s)
Weight & dimensions	Outer diameter	6 mm