

CAT5e F/UTP Network Cable 20m, Grey

CAT5e cables enables a convenient and reliable connection from one network device, such as switch, modem or router, to another or to the infrastructure at large through a patch panel, keystone jack or wall outlet. This cable are also used a lot in small office and home network and entertainment applications. These cables are tested up to 100Mhz (CAT5e standard) and are backwards compatible with CAT5 cables. They are produced with latch protection, which prevents the connector do be damaged when you install the cable through an installation with very less space. Furthermore this cable is manufactured with shielding. This protects against both EMI (electromagnetic interference). EMI can cause crosstalk between circuits, resulting in degradation of data, increased errors and slower transmission rates, but by using this shielded cable you will avoid this problem.



- F/UTP Shielding, protects again EMI (Electromagnetic interference)
- with Latch Protection
- with slimline strain relief, with gold plated PINs

Specifications

FeaturesAWG wire size64/7Cable length20 mCable lengthFUTP (FTP)Cable shieldingFUTP (FTP)Cable shieldingCatSeCable standardCatSeCanduct materialCoper-Clad Aluminium (CCA)Conductor typeMaleConnector 1RJ45Connector 1RJ45Connector 2 genderMaleConnector 2 genderMolFequency100 Mbit/sTedut colourRoyJackt materialNour Mbit/sPoduct orburCregPoduct colourReinMith ProtectionSindPoduct seriesRoun CableFequencyKink Protection strain relief and Latch ProtectionPoduct seriesSind Sind Sind Sind Sind Sind Sind Sind			
Cable shielding F/UTP (FTP) Cable standard CaSe Cable type CaSe Conductor material Copper-Clad Aluminium (CCA) Conductor type Stranded Connector 1 R145 Connector 1 gender Male Connector 2 gender Male Connector 2 gender Mole Data transfer rate 1000 Mbit/s Frequency 1000 Mbit/s Frequency Nol MHz Jacket material Polyvinyl chloride (PVC) Product colour Crey ROHS compliance Ves Porduct series Round Cable Technical features Kink Protection, strain relief and Latch Protection Verified 0.448 kg Height Verified 8 cm Werified 8 cm With Verified 8 cm With Verified 166 cm	Features	AWG wire size	26/7
Cable standardCatSeCable typeCatSeConductor materialCopper-Clad Aluminium (CCA)Conductor typeStrandedConnector 1R145Connector 1 genderMaleConnector 2 genderMaleConnector 2 genderNol Mbit/sFrequency1000 Mbit/sJacket materialPolyvinyl chloride (PVC)Product colourCreyRoHS complianceVesConse triesRound CableTechnical featuresNak Protection, strain relief and Latch ProtectionVerified164 cmHeight Verified8 cmHeight Verified8 cmWidt Verified166 cmPackaging dataQuatiy pe packIp Casi1p (s)		Cable length	20 m
Cable typeCa5eConductor materialCopper-Clad Aluminium (CCA)Conductor typeStrandedConductor typeMaleConnector 1RaSCConnector 2MaleConnector 2MaleData transfer rateMol Mbit/sProduct colourOrol Mbit/sRequencyOrol Mbit/sProduct colourGregProduct colourGregProduct colourStandedProduct colourNon CableProduct seriesSconded alume (Standed alume)Product seriesNon CableProduct seriesSconded alume)Product seriesSconded alume)Product seriesSconded alume)Product seriesSconded alume)Product seriesSconded alume)Product seriesSconded alume)Product seriesSconded alume)Sconded trained alumeSconded alume)Product seriesSconded alume)Sconded trained alumeSconded alume)Sconde trained alumeSconded alume) <th>Cable shielding</th> <th>F/UTP (FTP)</th>		Cable shielding	F/UTP (FTP)
Conductor materialCopper-Clad Aluminium (CCA)Conductor typeStrandedConnector 1RJ45Connector 1 genderMaleConnector 2 genderMaleConnector 2 genderMolo Mbit/sData transfer rate000 Mbit/sJacket materialPolyviryl chloride (PVC)Preduct colourGregRoHS complianceVesProduct seriesRound CableTechnical featuresNul Protection, strain relief and Latch ProtectionPreduct seriesScaweight VerifiedVerifiedScaweight VerifiedMich Protection, strain relief and Latch ProtectionPackage dimensiongLeptin VerifiedWeiffiedScameight VerifiedMich VerifiedScameight VerifiedMich Verified <th>Cable standard</th> <th>Cat5e</th>		Cable standard	Cat5e
Conductor typeStandedConnector 1R04Connector 1 genderMaleConnector 2 genderR04Connector 2 genderMoleData transfer rate000 Mbi/sFrequency100 Mbi/sJacket materialPolyvinyl chloride (PVC)Product colourR04R04S complianceSind CableTethnical featuresKink Protection strain relief and Latch ProtectionPackage dimensionsPoth VerifiedKeriffedSicanaHeight VerifiedSicanaKeriffedSica		Cable type	Cat5e
Connector 1 R345 Connector 1 gender Male Connector 2 gender R345 Connector 2 gender Male Data transfer rate 1000 Mbit/s Frequency 100 Mbit/s Jacket material Polyvinyl chloride (PVC) Product colour Grey RHS compliance Ves Verified Kink Protection, strain relief and Latch Protection Package dimensions Depth Verified 6448 kg Werified 8cm 164 cm Packaging data Quantity per pack 162 cm		Conductor material	Copper-Clad Aluminium (CCA)
Connector 1 genderMaleConnector 2R345Connector 2 genderMaleDat transfer rate100 Mbi/sFrequency00 MHzJacket materialPolyvinyl chloride (PVC)Product colourGregRoHS complianceVesProduct seriesRound CableTechnical featuresNei Nei Nei Nei Nei Nei Nei Nei Nei Nei		Conductor type	Stranded
Connector 2RJ45Connector 2 genderMaleData transfer rate000 Mbi/sFrequency100 MHzJacket materialPolyvinyl chloride (PVC)Product colourCreyRHS complianceVesCother featuresProduct seriesPackage dimensions (verified)Dept VerifiedPackage dimensions (verified)Dept VerifiedActor Streight Verified0.448 kgHeight Verified8 cmVettor Field16.6 cmPackaging dataQunity per packPackaging dataDept NergencePackaging dataData transferiedPackaging dataQunity per packPackaging dataData transferiedPackaging dataData t		Connector 1	RJ45
Connector 2 genderMaleConnector 2 genderMaleData transfer rate100 Mbit/sFrequency100 MHzJacket materialPolyvinyl chloride (PVC)Product colourGreyRoHS complianceYesProduct seriesRound CableTechnical featuresKink Protection, strain relief and Latch ProtectionPackage dimensionsDept Verified(verified)0.448 kgHeight Verified8 cmMith Verified16.6 cmPackaging dataQuantity pe packIn ConstructionIpc(s)		Connector 1 gender	Male
Data transfer rate1000 Mbit/sFrequency100 MHzJacket materialPolyvinyl chloride (PVC)Product colourGreyRoHS complianceYesProduct seriesRound CableTechnical featuresKink Protection, strain relief and Latch ProtectionPackage dimensions (verified)Depth VerifiedApril Depth Verified0.448 kgHeight Verified8 cmMith Verified16.6 cmPackaging dataQuantity per pack		Connector 2	RJ45
FrequencyIOO MHzJacket materialPolyinyl chloride (PVC)Product colourGreyRoHS complianceVesProduct seriesRound CableTechnical featuresKink Protection, strain relief and Latch ProtectionPackage dimensions (verified)Dept VerifiedAuge Verified8cmHeight Verified8cmVer		Connector 2 gender	Male
Jacket materialPolyvinyl chloride (PVC)Jacket materialPolyvinyl chloride (PVC)Product colourGreyRoHS complianceYesOther featuresProduct seriesTechnical featuresRound CableTechnical featuresKink Protection, strain relief and Latch ProtectionPackage dimensions (verified)Depth VerifiedPackage dimensions (verified)Depth VerifiedHeight Verified0.448 kgHeight Verified8 cmVidth Verified16.6 cmPackaging dataQuantity per packI pc(s)1pc(s)		Data transfer rate	1000 Mbit/s
Product colourGreyRoHS complianceYesOther featuresProduct seriesRound CableTechnical featuresKink Protection, strain relief and Latch ProtectionPackage dimensions (verified)Depth Verified16.4 cmGross Weight Verified0.448 kgHeight Verified8 cmWidth Verified16.6 cmPackaging dataQuantity per pack1 pc(s)		Frequency	100 MHz
RoHS complianceYesOther featuresProduct seriesRound CableTechnical featuresKink Protection, strain relief and Latch ProtectionPackage dimensions (verified)Depth Verified16.4 cmGross Weight Verified0.448 kgHeight Verified8 cmWidth Verified16.6 cmPackaging dataQuantity per pack1 pc(s)		Jacket material	Polyvinyl chloride (PVC)
Other featuresProduct seriesRound CableTechnical featuresKink Protection, strain relief and Latch ProtectionPackage dimensions (verified)Depth Verified16.4 cmCross Weight Verified0.448 kgHeight Verified8 cmWidth Verified16.6 cmPackaging dataQuantity per pack1 pc(s)		Product colour	Grey
Package dimensions (verified)Depth Verified16.4 cmCross Weight Verified0.448 kgHeight Verified8 cmWidth Verified16.6 cmPackaging dataQuantity per pack		RoHS compliance	Yes
Package dimensions (verified)Depth Verified16.4 cmCross Weight Verified0.448 kgHeight Verified8 cmWidth Verified16.6 cmPackaging dataQuantity per pack1 pc(s)	Other features	Product series	Round Cable
(verified)Gross Weight Verified0.448 kgHeight Verified8 cmWidth Verified16.6 cmPackaging dataQuantity per pack1 pc(s)		Technical features	Kink Protection, strain relief and Latch Protection
Packaging data Quantity per pack 0.448 kg 0.448 kg 0.448 kg 8 cm 16.6 cm 1 pc(s)		Depth Verified	16.4 cm
Width Verified 16.6 cm Packaging data Quantity per pack 1 pc(s)		Gross Weight Verified	0.448 kg
Packaging data Quantity per pack 1 pc(s)		Height Verified	8 cm
		Width Verified	16.6 cm
Product dimensions Net Weight (Product, kg) 0.348 kg	Packaging data	Quantity per pack	1 pc(s)
	Product dimensions	Net Weight (Product, kg)	0.348 kg



Vendor information	Brand Name	MicroConnect
	Warranty	25 Year(s)
Weight & dimensions	Outer diameter	5.5 mm



Other products in this series

Cable length	Black	Blue	Green	Grey
0.25	B-FTP50025S	B-FTP50025B	B-FTP50025G	B-FTP50025
0.3				B-FTP50030
0.5	B-FTP5005S	B-FTP5005B	B-FTP5005G	B-FTP5005
1.0	B-FTP501S	B-FTP501B	B-FTP501G	B-FTP501
1.5	B-FTP5015S		B-FTP5015G	B-FTP5015
2.0	B-FTP502S	B-FTP502B	B-FTP502G	B-FTP502
3.0	B-FTP503S	B-FTP503B	B-FTP503G	B-FTP503
5.0	B-FTP505S	B-FTP505B	B-FTP505G	B-FTP505
7.5	B-FTP5075S	B-FTP5075B	B-FTP5075G	B-FTP5075
10.0	B-FTP510S	B-FTP510B	B-FTP510G	B-FTP510
15.0	B-FTP515S	B-FTP515B	B-FTP515G	B-FTP515
20.0	B-FTP520S		B-FTP520G	B-FTP520
25.0			B-FTP525G	

Cable length	Orange	Pink	Purple	Red
0.25	B-FTP500250	B-FTP50025PI	B-FTP50025P	B-FTP50025R
0.3				
0.5	B-FTP500500	B-FTP5005PI	B-FTP50050P	B-FTP5005R
1.0	B-FTP501O	B-FTP501PI	B-FTP501P	B-FTP501R
1.5	B-FTP5015O	B-FTP5015PI	B-FTP5015P	B-FTP5015R
2.0	B-FTP502O	B-FTP502PI	B-FTP502P	B-FTP502R
3.0	B-FTP503O	B-FTP503PI	B-FTP503P	B-FTP503R
5.0	B-FTP505O	B-FTP505PI	B-FTP505P	B-FTP505R
7.5	B-FTP50750		B-FTP5075P	B-FTP5075R
10.0	B-FTP510O	B-FTP510PI	B-FTP510P	B-FTP510R
15.0	B-FTP515O	B-FTP515PI	B-FTP515P	B-FTP515R
20.0	B-FTP520O		B-FTP520P	B-FTP520R
25.0				

Cable length	White	Yellow
0.25	B-FTP50025W	B-FTP50025Y
0.3		



Cable length	White	Yellow
0.5	B-FTP5005W	B-FTP5005Y
1.0	B-FTP501W	B-FTP501Y
1.5	B-FTP5015W	B-FTP5015Y
2.0	B-FTP502W	B-FTP502Y
3.0	B-FTP503W	B-FTP503Y
5.0	B-FTP505W	B-FTP505Y
7.5	B-FTP5075W	B-FTP5075Y
10.0	B-FTP510W	B-FTP510Y
15.0	B-FTP515W	B-FTP515Y
20.0	B-FTP520W	B-FTP520Y
25.0		