


MPN: MC-USB3.0-F3B1

# PCIe USB3.0 3+1 Ports Expansion Card VL805

This production is a single chip USB 3.0 Host controller which enables a PCI Express equipped platform to interface with USB Super-Speed(5Gbps),High-Speed(480Mbps),Full-Speed(12Mbps), and Low-Speed (1.5Mbps) devices, Users can easy to connect your Mass Storage, Printer, Scanner , Hub, Camera and any other USB Devices to used.

## System Requirements

Linux/ Win7/ Win8/ Win8.1/ Win10 32bit or 64 bit / Windows® XP/ Vista



- Compliant to Universal Serial Bus 3.0 Specification Revision 1.0
- Compliant to Universal Serial Bus 2.0 Specifications
- Compliant to extensible Host Controller Interface Specification Revision 1.0
- Compliant with PCI Express base specification 2.0
- Support Legacy USB Function, Four Down-stream ports Support Super-Speed(SS)
- High-Speed (HS),Full-Speed (FS) and Low-Speed (LS)
- Max. 5V/900mA power output to each USB 3.0 Port
- 4-pin power connector for extra power
- Fully plug ,play and hot plug compatible

## Specifications

<b>Design</b>	<b>Internal</b>	Yes
<b>Features</b>	<b>Bandwidth</b>	5 Gbit/s
<b>Operational conditions</b>	<b>Operating temperature (T-T)</b>	5 - 35 °C
<b>Package dimensions (verified)</b>	<b>Depth Verified</b>	13 cm
	<b>Gross Weight Verified</b>	0.094 kg
	<b>Height Verified</b>	3.4 cm
	<b>Width Verified</b>	17.4 cm
<b>Packaging data</b>	<b>Drivers included</b>	Yes
	<b>Quantity</b>	1
<b>Ports &amp; interfaces</b>	<b>Host interface</b>	PCIe
	<b>Internal USB 3.2 Gen 1 (3.1 Gen 1) ports quantity</b>	1
	<b>Output interface</b>	USB 3.2 Gen 1 (3.1 Gen 1)
	<b>USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity</b>	4
<b>Power</b>	<b>Output current</b>	0.9 A
	<b>Output voltage</b>	5 V
<b>Product dimensions</b>	<b>Net Weight (Product, kg)</b>	0.09 kg
	<b>Product Depth</b>	7 cm
	<b>Product Width</b>	8 cm

<b>System requirements</b>	<b>Windows operating systems supported</b>	Yes
	<b>Vendor information</b>	
	<b>Brand Name</b>	MicroConnect
	<b>Warranty</b>	3 Year(s)