

NOTES:


ELECIICAL:

- (1). 100% CONTINUITY (OPEN, SHORT, MISSWIRE) ;
- (2). INSULATION RESISTANCE:300V, 5MΩ MIN;
- (3). CONDUCTIVE RESISTANCE: :5 Ω MAX;
- (4). 100% HDTV-DVD TEST:4K*2K@60HZ;
- (5). WIRE SURFACE PRINTING(White):/

CN1 (TYPE C)		CN2 (HDMI PCBA)		
B1, B12, A1, A12	10uF	G	V (VBus)	HDMI PCBA
B4, B9, A4, A9				
A2		A2		
A3		A3		
B2		B2		
B3		B3		
A10		A10		
A11		A11		
B10		B10		
B11		B11		
A5		A5		
B5		B5		
A6		A6		
A7		A7		
A8		A8		
B8		B8		
SHELL		DRAIN	SHELL	

⑧	PE BAG	PE BAG:W155*L175*T0.05mm	1	PCS
⑦	MINI TIE	TIE, METAL MATERIAL INSIDE, BLACK OUTSIDE	1	PCS
⑥	O-ring	O-ring GREEN COLOR	2	PCS
⑤	OUTER MOLD	87A TPU, COLOR FOR BLACK	2	PCS
④	INNER MOLD	LDPE, COLOR FOR WHITIE	2	PCS
③	CONNECTOR 2	HDMI 19P/MALE, HOUSING FOR BLACK PLASTIC, TERMINAL FOR Cu AND GOLD PLATED, THE SHELL FOR METAL AND GOLD PLATING+PCBA(IC CS5265)	1	PCS
②	CONNECTOR 1	USB TYPE C MALE, HOUSING FOR BLACK PLASTIC, TERMINAL FOR Cu AND GOLD PLATED, THE SHELL FOR METAL AND GOLD PLATING+10uF	1	PCS
①	TYPE C CABLE	(1/0.20BC*1P+AL)*4C+1/0.20BC*1P+1/0.20BC*4C+41/0.08BC*2C+AL, BLACK TPU JACKET, OD:4.8±0.2mm	1	PCS

Pack Draw:



- MPN: MC-USBCHDMI05 0,5m
- MPN: MC-USBCHDMI1 1m
- MPN: MC-USBCHDMI2 2m
- MPN: MC-USBCHDMI3 3m
- MPN: MC-USBCHDMI5 5m

NO.		Part name			Specifications describe		Dosage		UNIT		
Approved	Reviewer	Drawing	Drawing No.	TYO***		Product name					
Emil Olsen	Franck	Tsou	ITEM No.	MC-USBCHDMIxx		USB-C TO HDMI A/M CABLE L=**M(GOLD)					
			Customer Name								
			Unit	mm	Tolerance						X. ±1.00
			Graphic	⊕	X.X						±0.50

