

MPN: HDM19193FV1.4

## HDMI 1.4 Extension Cable, 3m

HDMI (High Definition Multimedia Interface) is one of the most used and acknowledged connections when transferring video and audio digitally from a source to a video display device or other compatible devices. This HDMI 1.4 cable is a High Performance and High Speed cable. It supports transfers up to 10.2 Gbps. It supports resolutions up to 4K@30Hz with HDCP 2.2, CEC, ARC and 3D. With this extension HDMI cable you can extend the installation without any signal loss.



- 4K@30Hz (3840\*2160p), including 3D video
- Gold-Plated Connectors
- Transfer rate : 10.2 Gbit/s
- HDCP 2.2
- Support ARC (Audio Return Channel)
- Support HDR (High Dynamic Range)
- Support CEC (Consumer Electronics Control)
- Integrated Ethernet channel which saves additional network or audio cables

## Specifications

### Features

<b>3D</b>	Yes
<b>Audio Return Channel (ARC)</b>	Yes
<b>AWG wire size</b>	30
<b>Cable length</b>	3 m
<b>Cable material</b>	Copper
<b>Connector 1</b>	HDMI Type A (Standard)
<b>Connector 1 form factor</b>	Straight
<b>Connector 1 gender</b>	Male
<b>Connector 2</b>	HDMI Type A (Standard)
<b>Connector 2 form factor</b>	Straight
<b>Connector 2 gender</b>	Male
<b>Connector contacts plating</b>	Gold
<b>Data transfer rate</b>	10.2 Gbit/s
<b>HDCP</b>	Yes
<b>HDCP version</b>	1.4/2.2
<b>HDMI Ethernet channel</b>	Yes
<b>HDMI version</b>	1.4
<b>High Dynamic Range (HDR) supported</b>	Yes
<b>Maximum resolution</b>	3840 x 2160 Pixels
<b>Product colour</b>	Black
<b>Quantity per pack</b>	1 pc(s)
<b>RoHS compliance</b>	Yes
<b>Other features</b>	
<b>Quantity</b>	1

<b>Package dimensions (verified)</b>	<b>Depth Verified</b>	21 cm
	<b>Gross Weight Verified</b>	0.156 kg
	<b>Height Verified</b>	3.5 cm
	<b>Width Verified</b>	26.7 cm
<b>Product dimensions</b>	<b>Net Weight (Product, kg)</b>	0.055999999999999994 kg
<b>Vendor information</b>	<b>Brand Name</b>	MicroConnect
	<b>Warranty</b>	25 Year(s)
<b>Weight &amp; dimensions</b>	<b>Cable diameter</b>	6 mm

## Other products in this series

Cable length	
0.5	HDM19190.5FV1.4
1.0	HDM19191FV1.4
1.5	HDM19191.5FV1.4
2.0	HDM19192FV1.4
3.0	HDM19193FV1.4
5.0	HDM19195FV1.4