

MPN: DP-HDMI-2000V1.40P

# Premium Optic Fiber DisplayPort 1.4 -HDMI 2.0 Cable, 20m

This active optical DisplayPort 1.4 to HDMI 2.0 cable connects devices across long distances up to 100m without data loss – even in sensitive applications. It contains both fiber optic and copper cores, it is lightweight, flexible and has a ultra-small bend radius which makes it perfectly suitable for all kinds of installations.

- Supporting 4K60Hz, 18Gbps
- Sampling : YUV 4:4:4
- Outer Diameter: 4,5mm, very flexible
- Compatible with HDMI 2.0 standard
- Supports EDID, HDCP (2.2), HDR (High Dynamic Range ), HEC, ARC
- Hybrid optical cable with fibre and copper wire
- Has Source & Display clearly printed on the connector for easy identification
- No loss of signal delivering crystal clear digital images instantly

- Low RFI / EMI profile for sensitive applications
- Self-detecting function for EDID information
- DisplayPort : Source / HDMI: Display

Specifi	cations
---------	---------

### Features

3D	Yes	
Bandwidth	18000 MB/s	
Cable length	20 m	
Cable material	Fiber optic	
Connector 1	DisplayPort	
Connector 1 gender	Male	
Connector 2	HDMI Type A (Standard)	
Connector 2 gender	Male	
Connector contacts plating	Gold	
Data transfer rate	18 Gbit/s	
DisplayPort Content Protection (DPCP)	Yes	
DisplayPort version	1.4	
HDCP version	2.2	
HDMI version	2.0	
High Dynamic Range (HDR) supported	Yes	
Jacket material	Polyvinyl chloride (PVC)	
Maximum resolution	3840 x 2160 Pixels	
Plug and Play	Yes	
Product colour	Black	
RoHS compliance	Yes	
Supported video modes	480p, 720p, 1080i, 1080p, 2160p	



Package dimensions (verified)	Depth Verified	22.8 cm
	Gross Weight Verified	0.644 kg
	Height Verified	4.3 cm
	Width Verified	23.9 cm
Product dimensions	Net Weight (Product, kg)	0.544 kg
Vendor information	Brand Name	MicroConnect
	Warranty	25 Year(s)



## Other products in this series

Cable length	
10.0	DP-HDMI-1000V1.40P
15.0	DP-HDMI-1500V1.40P
20.0	DP-HDMI-2000V1.40 P
30.0	DP-HDMI-3000V1.40 P



## Other images

