

MPN: BNC-HDSDI-10M

## 12G-SDI BNC cable 10m

MicroConnect 12G SDI cable supports signals from 12G-SDI, 6G-SDI, HD-SDI and 3G-SDI. The cable is designed for use with your professional equipment that requires an SDI connection. Support 4K60Hz for resolutions up to 4096x2160 & Full HD 1080p.

75ohm

- Designed in Denmark
- Flexible and durable: Best suited to mobile HD application
- Designed for withstanding repeated bending
- Stranded center conductor
- High-density double-braided shield.



## **Specifications**

| Features           | Cable length               | 10 m         |
|--------------------|----------------------------|--------------|
|                    | Connector 1                | BNC          |
|                    | Connector 1 gender         | Male         |
|                    | Connector 2                | BNC          |
|                    | Connector 2 gender         | Male         |
| Package dimensions | Depth (package,cm)         | 2.5 cm       |
|                    | Gross Weight (Package, kg) | 0.31 kg      |
|                    | Height (package,cm)        | 28 cm        |
|                    | Width (package,cm)         | 28 cm        |
| Product dimensions | Net Weight (Product, kg)   | 0.3 kg       |
| Vendor information | Brand Name                 | MicroConnect |
|                    | Warranty                   | 25 Year(s)   |



## Other products in this series

| Cable length |                |
|--------------|----------------|
| 1.0          | BNC-HDSDI-1M   |
| 2.0          | BNC-HDSDI-2M   |
| 3.0          | BNC-HDSDI-3M   |
| 5.0          | BNC-HDSDI-5M   |
| 10.0         | BNC-HDSDI-10M  |
| 15.0         | BNC-HDSDI-15M  |
| 20.0         | BNC-HDSDI-20M  |
| 100.0        | BNC-HDSDI-100R |



## Other images

